

PLINTENKIT FLOOR®



PRODUCT DESCRIPTION

A professional, flexible, paintable construction adhesive based on MSP with an extremely high initial tack.

APPLICATION

PLINTENKIT is a high quality product for structural bonding for example skirting, panels for walls, floors, ceilings, etc. Stamping or terminals in most cases not necessary. Bonding of virtually all common construction materials and (even wet) surfaces. Indoor and outdoor use without a border area pollution. Paintable with most types of acrylic latex and Alkyd. Bonding plaster, glass, mirrors and many plastics (acrylic), (natural) stone, concrete, wood and many metals on various substrates and themselves.

Examples: Wall coverings, ceiling panels, insulation panels (mineral wool, foam, pur, ps, etc), building, ornaments, frames, sills, window sills, baseboards, mouldings, roof and facade elements.

DIRECTIONS FOR USE

Editing substrate, the substrate must be clean, dust and grease. Using PRIMER ® CS 60 required only there where extreme structural requirements in combination with very porous surfaces. Not recommended substrates: PE, PP and Teflon. Tools: syringe tube with hand or airgun. Adhesives and mounting: application in stripes, dots or full level. Tamping (if necessary fix) and let harden. Do not use below +5°C. Remove wet adhesive residue CLEANER CS 60 ®.

PROPERTIES

Temperature resistance: from -40°C to +100°C. Moisture and frost resistance: good. Chemical resistance: resistant to all weather, UV light, short action of dilute acids, alkalis and salts. Overcoatability: good. Elasticity: permanently elastic.

TECHNICAL INFORMATION

Basic Material	: MSP.
Color	: white, RAL 9001.
Density	: 1569kg / m ³ .
Application rate	: 3 mm/6.3 Bar.
Skin	: after about 10 minutes at +20°C.
Tack free time	: after about 2 hours.
Hardness	: about 60 shore A.
Shrinkage	: none.
Curing	: approx 2-3 mm per 24 hours.
Elongation	: 300%.
Internal strength (directly)	: about 0.01 N/mm ² .
Tensile strength	: about 2.2 N/mm ² .
Mildew resistant	: excellent.

SHELF LIFE

PLINTENKIT has, in a sealed container in a cool frost free place, at least 12 months shelf life after manufacturing.

BIJLARD®
PROFESSIONAL ADHESIVES

PACKAGING

Cartridges of 290 ml.

Consumption

Using PLINTENKIT V-necked approximately 7.25 m¹ per cartridge.

Our processing advice is based on extensive research and practical experience. We can accept no liability for the results obtained and / or any damage resulting from the use of this product because of the wide range of materials and circumstances in which the glue is used. Nevertheless we would be pleased to advise you.



Clean indoor air – for your health and environmental protection!

People tend to spend more and more time indoors. Therefore, indoor air quality and emissions from indoor installation materials on floors and walls are increasingly becoming more important.

In order to achieve a healthy living environment it is important to pay attention to ingredients of materials for flooring installation, and construction products such as insulation panels, adhesives or seals. To ensure greatest possible protection regarding health, environmental and indoor air hygiene, you should rely on materials awarded the EMICODE® label. They are very low in emissions, meet the strictest tolerances and standards and are permanently monitored by independent inspection bodies.

As a result, EMICODE® guarantees a clean and safe indoor air quality for years to come – for a healthy and comfortable indoor climate.

BIJLARD®
PROFESSIONAL ADHESIVES