

BIJLARD MS PRIMER CS60



PRODUCT DESCRIPTION

MS PRIMER CS60 is a 1-component moisture-hardening primer based on MSP.

APPLICATION

MS PRIMER CS60 is especially suitable for the pre-treatment of wooden battens and for surfaces such as wood, stone and concrete

PROCESSING

The surface must be clean, dry and free of grease. The CM% (moisture content) in a wooden substrate must not exceed 18%. Apply with brush or roller.

Minimum temperature: + 10°C. The relative humidity must not exceed 85% at a temperature of + 10°C.

CHARACTERISTICS

Very good mechanical resistance.

Resistant to moisture and chemicals.

Excellent adhesion.

Drying at least 30 minutes.

TECHNICAL INFORMATION

Basic raw material	: MSP
Color	: transparent and black
Processing temperature	: + 10° C to + 30° C
Specific gravity	: 1.0 kg/m ³
Consumption	: approx. 6-10 m ² /kilo

SHELF LIFE

MS PRIMER CS60 has a shelf life of 12 months after production in unopened packaging in a cool, frost-free place. Always process in order of receipt.

PACKAGING

1 liter can

Our processing recommendations are based on extensive research. Due to the wide variety of materials and conditions under which gluing takes place, we cannot accept liability for the results

BIJLARD®
PROFESSIONAL ADHESIVES

obtained and/or any damage that may result from the use of the product. We are at your disposal with advice.

BIJLARD®
PROFESSIONAL ADHESIVES

Bijlard International • Platinastraat 141, 2718 SR Zoetermeer • The Netherlands • Phone: +31 (0)79 343 75 38 • info@bijlard.com • www.bijlard.com
ING bank: 068.60.31.156 • IBAN nr.: NL65INGB0686031156 • SWIFT: INGBNL 2A • BTW nr.: NL804836024 B.01 • KvK 's Gravenhage: 27124597