

BIJLARD CS HIGH TACK®



PRODUCT DESCRIPTION

A professional, flexible, paintable construction adhesive based on MSP with an extremely high initial tack.

DIRECTION FOR USE

CS HIGH TACK® is a high quality product for structural bonding example plates, skirting, panels for walls, floors, ceilings, etc. Stamping or terminals in most cases not necessary. Bonding of virtually all common construction materials and (even wet) surfaces. Indoor and outdoor use without a border area pollution. Paintable with most types of acrylic latex and Alkyd. Bonding plaster, glass, mirrors and many plastics (acrylic), (natural) stone, concrete, wood and many metals on various substrates and themselves.

Examples: Wall coverings, ceiling panels, insulation panels (mineral wool, foam, pur, ps, etc), building, ornaments, frames, sills, window sills, baseboards, moldings, roof and facade elements.

PROCESSING

Editing substrate, the substrate must be clean, dust and grease. Using PRIMER® CS 60 required only there where extreme structural requirements in combination with very porous surfaces. Not recommended substrates: PE, PP and Teflon.

Tools: syringe tube with hand or luchtkitspuit process.

Adhesives and mounting: application in stripes, dots or full level. Tamping (if necessary fix) and let harden. Do not use below +5°C. Remove wet adhesive residue CLEANER CS 60®.

TECHNICAL INFORMATION

| | |
|-------------------------------|-----------------------------------------------------------------------------|
| Temperature resistance | : from -40°C to +100°C |
| Moisture and frost resistance | : good |
| Chemical resistance | : resistant to all weather, UV light, short action of dilute acids, alkalis |
| and | salts |
| Overcoatability | : good |
| Elasticity | : permanently elastic |
| Basic Material | : MSP |
| Color | : white, RAL 9001 |
| Density | : 1569kg / m ³ |
| Application rate | : 3 mm/6.3 Bar |
| Skin | : after about 10 minutes at +20°C |
| Tack free time | : after about 4 hours |

BIJLARD®
PROFESSIONAL ADHESIVES

| | |
|------------------------------|--------------------------------|
| Hardness | : about 60 shore A |
| Shrinkage | : none |
| Curing | : approx 2-3 mm per 24 hours |
| Elongation | : 330%. |
| Internal strength (directly) | : about 0.01 N/mm ² |
| Tensile strength | : about 2.2 N/mm ² |
| Mildew resistant | : excellent |

CONSUMPTION

Using High Tack V-necked approximately 7.25 m¹ per cartridge.

SHELF LIFE

CS HIGH TACK® has, in a sealed container in a cool frost free place, at least 12 months shelf life after manufacturing.

PACKAGING

Cartridges of 290 ml.

Our processing advice is based on extensive research and practical experience. We can accept no liability for the results obtained and / or any damage resulting from the use of this product because of the wide range of materials and circumstances in which the glue is used. Nevertheless we would be pleased to advise you.



BIJLARD®
PROFESSIONAL ADHESIVES