

BIJLARD CS HIGH TACK®



PRODUCT DESCRIPTION

A professional, flexible, paintable construction adhesive based on MSP with an extremely high initial tack.

CS HIGH TACK FAST® is a high-quality MS polymer adhesive with extremely high initial tack for the fast and powerful bonding of panels, skirting boards and wall, floor and ceiling elements. In many cases, temporary support or clamping is not required. Suitable for indoor and outdoor applications on various substrates, including slightly damp surfaces. Paintable with most acrylic and alkyd paints. Adheres to materials such as gypsum, glass, mirrors, acrylics, natural stone, concrete, wood and various metals. Applications: wall cladding, ceiling panels, insulation panels, skirting boards, thresholds, window sills, ornaments, roof elements and façade elements.

PROCESSING

Editing substrate, the substrate must be clean, dust and grease. Using PRIMER® CS 60 required only there where extreme structural requirements in combination with very porous surfaces. Not recommended substrates: PE, PP and Teflon.

Tools: syringe tube with hand or luchtkitspuit process.

Adhesives and mounting: application in stripes, dots or full level. Tamping (if necessary fix) and let harden. Do not use below +5°C. Remove wet adhesive residue CLEANER CS 60®.

TECHNICAL INFORMATION

Temperature resistance	: from -40°C to +100°C.
Moisture and frost resistance	: good.
Chemical resistance	: resistant to all weather, short action of dilute acids, alkalis and salts.
Overcoatability	: good.
Elasticity	: permanently elastic.
Basic Material	: MSP
Color	: white, black
Density	: 1569kg / m ³
Application rate	: 3 mm/6.3 Bar
Skin	: after about 10 minutes at +20°C
Tack free time	: after about 4 hours

BIJLARD®
PROFESSIONAL ADHESIVES

Hardness	: about 60 shore A
Shrinkage	: none
Curing	: approx 2-3 mm per 24 hours
Elongation	: 330%.
Internal strength (directly)	: about 0.01 N/mm ²
Tensile strength	: about 2.2 N/mm ²
Mildew resistant	: excellent

CONSUMPTION

Using High Tack V-necked approximately 7.25 m¹ per cartridge.

SHELF LIFE

CS HIGH TACK FAST ® has, in a sealed container in a cool frost free place, at least 12 months shelf life after manufacturing.

PACKAGING

Cartridges of 290 ml.
Sausages 600nl.
Drum 200L



Our processing advice is based on extensive research and practical experience. We can accept no liability for the results obtained and / or any damage resulting from the use of this product because of the wide range of materials and circumstances in which the glue is used. Nevertheless we would be pleased to advise you.

BIJLARD®

PROFESSIONAL ADHESIVES