

BIJLARD 0023 GLUE SPRAY HIGH TACK



PRODUCT DESCRIPTION

Is a contact adhesive with a high initial strength and therefore very suitable for bonding many different flexible foams like latex-, polyether- and polyurethane foam. The adhesive can also be applied for fixation of carpet, underpadding and many different carpet tiles. Furthermore, the adhesive can be used for bonding materials like paper, textile, cardboard, artificial leather, etc. to each other as well as in combination. Not recommended for polystyrene foam. The spray pattern and volume of adhesive can be changed by turning the nozzle in the given positions.

DIRECTIONS FOR USE

Surfaces must be dry and free from dust. Shake can well before use.

Flexible foams: apply adhesive on both surfaces. At **+20°C** and 65% rel. humidity a drying time of only 30 sec. is sufficient; the bond can be made almost instantly.

Non porous materials (like artificial leather): apply adhesive 2-sided. Drying time is approx. 2 minutes. Join together; press firmly. To keep nozzle clear after use, hold the aerosol upside down and push button until no adhesive comes out anymore.

TECHNICAL INFORMATION

Based on : synthetic SBR-rubber in solution.
Specific weight : 0.84 kg/L \pm 0.02 kg/L.
Solids contents : 30 \pm 0.5%.
Physical form : aerosol.
Viscosity : **20 - 50 mPa.s** (**+20° C**).
Colour : transparent yellow.
Drying time : approx. 2 min. (**+20° C**) (2-sided).
Open time : max. 15 min.
Heat resistance : \pm **+60° C**.

SHELF LIFE

1 year at **+20°C** in unopened package.

CLEANING

VERDUNNER.

PACKAGING

500 ml aerosol.

Our processing advice is based on extensive research and practical experience. We can accept no liability for the results obtained and / or any damage resulting from the use of this product because of the wide range of materials and circumstances in which the glue is used. Nevertheless we would be pleased to advise you.

BIJLARD®
PROFESSIONAL ADHESIVES