

# 0099 SBR sprayable adhesive

## PRODUCT DESCRIPTION

Is a spray able contact adhesive based on synthetic rubber. The adhesive has a wide range of applications and is ideal for bonding:

- Fabrics;
- Carpet, carpet tiles, carpet underlay;
- Foam (flakes, sessions, backing rods, etc.);
- Paper, cardboard (closing and stacking boxes);
- Insulation in construction and interior;
- Polystyrene Foam;
- Textiles, felt etc.
- Posters, reproductions;
- Plastic films.

## DIRECTIONS FOR USE

The materials for bonding must be dry, dust- and fat free. Spray from a distance of about 20 cm. With polystyrene a greater distance should be kept. In cold seasons glue and materials should be acclimatized to room temperature. It is recommended to shake or stir before usage.

Permanent bonding: Apply a thin layer of glue on both sides. After approximately 5 minutes drying time, both surfaces can be joint. Maximum open time is 45 minutes. Non-permanent bonding:

Spray a thin, even layer on one of the surfaces. Dry shortly before merging parts. The bond can be abolished without damaging the surfaces. Not recommended for outdoor use.

## TECHNICAL INFORMATION

Based on : SBR-rubber and resin in solution.  
Specific weight : 0.75± 0.02 Kg/L.  
Solid contents : 23 ± 0,5 %.  
Physical form : thin liquid.  
Viscosity : 50 – 200 mPa.s.  
Colour : milky white.  
Drying time : approx. 5 min. +20°C.  
Open time : max. 45 min.  
Heat resistance : +80°C stress test.

## SHELF LIFE

1 year at +20°C in unopened package..

## CLEANING

VERDUNNER.

## PACKAGING

25 L. and 200 L.

**Our processing advice is based on extensive research and practical experience. We can accept no liability for the results obtained and / or any damage resulting from the use of this product because of the wide range of materials and circumstances in which the glue is used. Nevertheless we would be pleased to advise you.**

**BIJLARD**®  
**PROFESSIONAL ADHESIVES**