

BIJLARD CS 60®



PRODUCT DESCRIPTION

A professional, flexible, paintable glue, assembly and sealant based on MSP.

DIRECTIONS FOR USE

CONSTRUCTION SEALER 60® is a high-quality product for bonding, mounting and the durable finishing of joints and connections. Suitable for interior and exterior applications and applicable to almost all substrates, including slightly damp surfaces. Adheres to: façade panels, glass, mirrors, many plastics (such as acrylic), natural stone, concrete, wood and various metals. Ideal for fixing skirting boards, paneling, window sills, thresholds and insulation boards. Also suitable for neatly finishing gaps, joints and connections where a flexible and durable solution is required. Paintable with most acrylic and alkyd paints.

PROCESSING

Editing substrate, the substrate must be clean, dust and grease are. Using PRIMER CS 60® is only necessary where extreme structural requirements are combined with very porous surfaces eg by bonding of cladding. Not recommended substrates: PE, PP and Teflon. Tools: syringe tube with hand or hand-airpistol. Adhesives and mounting: application in stripes or dots. Tamping and / or fix and let harden. Do not use below 5 ° C. Remove wet adhesive residue CLEANER CS 60®. Sealing: For optimum performance of the kit, the joint as deep as wide make at least 5 mm. Sealant with a wet finger or a wet spatula.

TECHNICAL INFORMATION

Moisture and frost resistance	: good.
Chemical resistance alkalis	: resistant to all weather, UV light, short action of dilute acids, and salts.
Overcoatability	: good.
Elasticity	: permanently elastic.
Basic Material	: moisture hardening MSP Polymers
Color	: brown, gray, white, black. Other colors available on request.
Density	: 1480 kg/m ³
Skin	: approx 10 min.
Tack free time	: approx 60 min.
Hardness	: approx 60 grams shore A
Shrinkage	: none
By Harding	: approx 2 mm per 24 hours
Elongation	: 300%
Tensile strength	: about 2.2 N/mm ²
Temperature resistance	: from -40°C to +100°C

BIJLARD®
PROFESSIONAL ADHESIVES

SHELF LIFE

CONSTRUCTION SEALER 60[®] is in a sealed container in a cool frost free place, at least 9 months shelf life after manufacturing.

PACKAGING

Cartridges of 290 ml syringe and sausages of 600 ml.



Our processing advice is based on extensive research and practical experience. We can accept no liability for the results obtained and / or any damage resulting from the use of this product because of the wide range of materials and circumstances in which the glue is used. Nevertheless we would be pleased to advise you.

BIJLARD[®]
PROFESSIONAL ADHESIVES