



SAFETY DATA SHEET

Bijlard Spuitlijm (Transparent)

According to Regulation (EC) No 1907/2006, Annex II, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Bijlard Spuitlijm (Transparent)

UFI UFI: JQSJ-7CY5-V00V-GGC1

Created: 7/5/2015

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Sprayable contact adhesive

Uses advised against Applications involving the use of naked flames and static discharges Non-industrial, non-professional uses.

1.3. Details of the supplier of the safety data sheet

Supplier Bijlard International
Platinastraat 141
2718 SR Zoetermeer
The Netherlands
+31 79 343 7538
+31 79 343 7539
info@bijlard.com

1.4. Emergency telephone number

Emergency telephone +31 (0) 79-3437538

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225

Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Hazard pictograms



Signal word

Danger

Bijlard Spuitlijm (Transparent)

Hazard statements	<p>EUH208 Contains ROSIN. May produce an allergic reaction.</p> <p>H225 Highly flammable liquid and vapour.</p> <p>H319 Causes serious eye irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p>
Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P243 Take action to prevent static discharges.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P280 Wear protective clothing, gloves, eye and face protection.</p> <p>P273 Avoid release to the environment.</p> <p>P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p>
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
Contains	Hydrocarbons, C6-C7, isoalkanes,cyclics,<5% n-hexane, BUTANONE, acetone
Supplementary precautionary statements	<p>P242 Use non-sparking tools.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P308+P313 IF exposed or concerned: Get medical advice/ attention.</p> <p>P404 Store in a closed container.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.1. Substances

Content

3.2. Mixtures

Hydrocarbons, C6-C7, isoalkanes,cyclics,<5% n-hexane			40-50%
CAS number: —	EC number: 926-605-8	REACH registration number: 01-2119486291-36	
This is a complex mixture of constituents, a UVCB substance of variable composition.Contains cyclohexane (CAS 110-82-7) 70-80% and n-hexane <5%			
Classification Flam. Liq. 2 - H225 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411			

Bijlard Spuitlijm (Transparent)

BUTANONE 20-30%		
CAS number: 78-93-3	EC number: 201-159-0	REACH registration number: 01-2119457290-43-XXXX
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336		
ACETONE 10-20%		
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49-XXXX
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336		
Magnesium Oxide <1.0%		
CAS number: 1309-48-4	EC number: 215-171-9	
Classification Not Classified		
ROSIN <1.0%		
CAS number: 8050-09-7	EC number: 232-475-7	REACH registration number: 01-2119480418-32-XXXX
Classification Skin Sens. 1 - H317		
Talc <0.1%		
CAS number: 14807-96-6	EC number: 238-877-9	
Classification Acute Tox. 4 - H332 STOT SE 3 - H335		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Remove affected person from source of contamination. Remove contaminated soaked clothing immediately and dispose of safely
Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Bijlard Spuitlijm (Transparent)

Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if any discomfort continues.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information	Chemical burns must be treated by a physician. Get medical attention immediately.
Inhalation	Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	May cause stomach pain or vomiting.
Skin contact	Prolonged contact may cause redness, irritation and dry skin.
Eye contact	May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Carbon dioxide (CO ₂). Alcohol-resistant foam. Powder. Water spray, fog or mist.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	The product is highly flammable.
Hazardous combustion products	When heated, vapours/gases hazardous to health may be formed.

5.3. Advice for firefighters

Protective actions during firefighting	Move containers from fire area if it can be done without risk. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.
Special protective equipment for firefighters	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Eliminate all sources of ignition. Avoid inhalation of vapours and contact with skin and eyes. Take precautionary measures against static discharges. This product is a sprayable product and if applied in such away, appropriate PPE and engineering measures should be taken to protect operators from the vapours, mists, aerosols, droplets, fume, gas, spray
-----------------------------	--

6.2. Environmental precautions

Environmental precautions	Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. Do not discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment.
----------------------------------	--

Bijlard Spuitlijm (Transparent)

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. Collect and dispose of spillage as indicated in Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Protect from freezing and direct sunlight. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store in tightly-closed, original container.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Usage description This product is a sprayable product and if applied in in such away, appropriate PPE and engineering measures should be taken to protect operators from the vapours, mists, aerosols, droplets, fume, gas, spray. Contact with skin and eyes and inhalation of vapours must be avoided under all circumstances.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

BUTANONE

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 600 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 300 ppm(Sk) 899 mg/m³(Sk)

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

Magnesium Oxide

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³

Short-term exposure limit (15-minute): WEL

ROSIN

Long-term exposure limit (8-hour TWA): WEL 0,05 mg/m³

Short-term exposure limit (15-minute): WEL 0,15 mg/m³

Sen

Talc

Long-term exposure limit (8-hour TWA): WEL 1 mg/m³ respirable dust

Long-term exposure limit (8-hour TWA): WEL 1 mg/m³

CYCLOHEXANE

Bijlard Spuitlijm (Transparent)

Long-term exposure limit (8-hour TWA): WEL 100 ppm 350 mg/m³

Short-term exposure limit (15-minute): WEL 300 ppm 1050 mg/m³

HEXANE-norm

Long-term exposure limit (8-hour TWA): WEL 20 ppm 72 mg/m³

Short-term exposure limit (15-minute): WEL

WEL = Workplace Exposure Limit.

Sen = Capable of causing occupational asthma.

Ingredient comments

WEL = Workplace Exposure Limits

BUTANONE (CAS: 78-93-3)

DNEL	Industry - Inhalation; Short term local effects: 600 mg/kg/day
	Industry - Dermal; : 1161 mg/kg/day
	Consumer - Dermal; : 412 mg/kg/day
	Consumer - Inhalation; : 106 mg/m ³
	Consumer - Dermal; Long term systemic effects: 31 mg/kg
PNEC	- Fresh water; 55.8 mg/l
	- Sediment (Marinewater); 284.74 mg/kg
	- Soil; 22.5 mg/kg
	marine water; 55.8 mg/l
	Intermittent release; 55.8 mg/l
	Sediment (Freshwater); 284.7 mg/kg
	STP; 709 mg/l
	- Food. Secondary poisoning; 1000 mg/kg

ACETONE (CAS: 67-64-1)

DNEL	Industry - Dermal; Long term : 186 mg/kg/day
	Industry - Inhalation; Short term : 2420 mg/m ³
	Industry - Inhalation; Long term : 1210 mg/m ³
	Consumer - Oral; Long term : 62 mg/kg/day
	Consumer - Dermal; Long term : 62 mg/kg/day
	Consumer - Inhalation; Long term : 200 mg/m ³
PNEC	- Fresh water; 10.6 mg/l
	- marine water; 1.06 mg/l
	- Intermittent release; 21 mg/l
	- Sediment (Freshwater); 30.4 mg/kg
	- Sediment (Marinewater); 3.04 mg/kg
	- STP; 100 mg/l
	- Soil; 29.5 mg/kg

CYCLOHEXANE (CAS: 110-82-7)

Ingredient comments

WEL = Workplace Exposure Limits

Bijlard Spuitlijm (Transparent)

DNEL

Consumer - Oral; Long term systemic effects: 59.4 mg/kg/day
 Consumer - Dermal; Long term systemic effects: 1186 mg/kg/day
 Industry - Dermal; Long term systemic effects: 2016 mg/kg/day
 Consumer - Inhalation; Short term local effects: 412 mg/m³
 Consumer - Inhalation; Short term systemic effects: 412 mg/m³
 Industry - Inhalation; Short term systemic effects: 700 mg/m³
 Industry - Inhalation; Short term local effects: 700 mg/m³
 Industry - Inhalation; Long term local effects: 700 mg/m³
 Industry - Inhalation; Long term systemic effects: 700 mg/m³

PNEC

Industry - Fresh water; 0.207 mg/l
 Industry - Sediment (Freshwater); 3.627 mg/l
 Industry - STP; 3.24 mg/l
 Industry - Soil; 2.99 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. Dust may form explosive mixture with air. Take precautionary measures against static discharges.

Eye/face protection

The following protection should be worn: Chemical splash goggles.

Hand protection

To protect hands from chemicals, gloves should comply with European Standard EN374. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves made of the following material: Butyl rubber. Protective gloves should have a minimum thickness of up to 0.64 mm. The selected gloves should have a breakthrough time of up to 4hr. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear apron or protective clothing in case of contact.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station. Provide eyewash station and safety shower. Wash contaminated clothing before reuse. Use appropriate skin cream to prevent drying of skin. Wash promptly if skin becomes contaminated. Change work clothing daily before leaving workplace.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P3.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Liquid.

Colour

Yellowish.

Bijlard Spuitlijm (Transparent)

Odour	Characteristic.
Odour threshold	Not available. Not available.
pH	Not available. Not determined.
Melting point	Not available.
Initial boiling point and range	80°C @ 760 mm Hg
Flash point	-20°C
Evaporation rate	MODERATE
Evaporation factor	Not available.
Upper/lower flammability or explosive limits	No information available.
Other flammability	No information available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	0.82 @ °C
Bulk density	Not available.
Solubility(ies)	Not available. Insoluble in water. Soluble in the following materials: Organic solvents.
Partition coefficient	Not available.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not available.
Viscosity	>20 m ² /s @ 40°C 16.4 mPa s @ 40°C
Explosive properties	No information available.
Comments	Information given is applicable to the product as supplied. Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.
Density	
Relative vapour density	
Water solubility	
Viscosity, dynamic	
<u>9.2. Other information</u>	
Refractive index	Not applicable.
Particle size	Not available.
Molecular weight	Not applicable.
Volatility	Not available.
Critical temperature	Not available.
Solvent content:	
Volatile organic compound	Not available.
Solids content:	

Bijlard Spuitlijm (Transparent)

Water:

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions No potentially hazardous reactions known. Avoid heat.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. When heated, vapours/gases hazardous to health may be formed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects Information given for the mixture in sect 3 is based upon the results of the calculation method. Some of the information given is also taken from data given for the individual ingredients of the mixture.

Acute toxicity - oral

Notes (oral LD₅₀) Not determined.

Acute toxicity - dermal

Notes (dermal LD₅₀) Not determined.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Not determined.

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Causes eye irritation.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Bijlard Spuitlijm (Transparent)

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

Vapour from this product may be hazardous by inhalation. Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion

Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

Skin contact

Prolonged contact may cause dryness of the skin. Repeated exposure may cause skin dryness or cracking.

Eye contact

Irritating to eyes.

Acute and chronic health hazards

Prolonged contact may cause redness, irritation and dry skin. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Route of exposure

Ingestion. Inhalation Skin and/or eye contact

Target organs

Brain Respiratory system, lungs Mucous membranes Skin

Medical symptoms

Skin irritation. Irritation of eyes and mucous membranes. Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting.

Medical considerations

Skin disorders and allergies. Convulsions. Central nervous system depression. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Toxicological information on ingredients.

Hydrocarbons, C6-C7, isoalkanes,cyclics,<5% n-hexane

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >5000 mg/kg, Oral,

Acute toxicity - dermal

Notes (dermal LD₅₀) No information available.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) No information available.

Skin corrosion/irritation

Bijlard Spuitlijm (Transparent)

Skin corrosion/irritation May cause skin irritation.

Serious eye damage/irritation

Serious eye damage/irritation Irritating effect on the eyes

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways.

BUTANONE

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >2193 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >5000 mg/kg, Dermal, Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 34.0

Species Rat

ATE inhalation (vapours mg/l) 34.0

Skin corrosion/irritation

Skin corrosion/irritation Not irritating.

Serious eye damage/irritation

Bijlard Spuitlijm (Transparent)

Serious eye damage/irritation	Causes eye irritation.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Not sensitising.
<u>Skin sensitisation</u>	
Skin sensitisation	Not sensitising.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Genotoxicity - in vivo	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	Carcinogenicity in humans is not expected.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	A single exposure may cause the following adverse effects: Drowsiness, dizziness, disorientation, vertigo.
Target organs	Central nervous system
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Based on available data the classification criteria are not met.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.

ACETONE

<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	5,800.0
Species	Rat
ATE oral (mg/kg)	5,800.0
<u>Acute toxicity - dermal</u>	
Notes (dermal LD₅₀)	LD ₅₀ >15800 mg/kg, Dermal, Rabbit
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC₅₀ vapours mg/l)	76.0
Species	Rat
ATE inhalation (vapours mg/l)	76.0

Bijlard Spuitlijm (Transparent)

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met. Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye damage.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Carcinogenicity in humans is not expected.

Reproductive toxicity

Reproductive toxicity - fertility This substance has no evidence of toxicity to reproduction.

Reproductive toxicity - development This substance has no evidence of toxicity to reproduction.

Specific target organ toxicity - single exposure

STOT - single exposure A single exposure may cause the following adverse effects: Drowsiness, dizziness, disorientation, vertigo.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure. NOAEL 900 mg/kg/day, Oral, Rat NOAEC 22500 mg/m³, Inhalation, Rat

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

ROSIN

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >2000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2000 mg/kg, Dermal, Rat

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Data lacking.

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Bijlard Spuitlijm (Transparent)

Serious eye damage/irritation	Based on available data the classification criteria are not met.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Based on available data the classification criteria are not met.
<u>Skin sensitisation</u>	
Skin sensitisation	May cause an allergic skin reaction.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Genotoxicity - in vivo	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	Based on available data the classification criteria are not met.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Based on available data the classification criteria are not met.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.

XYLENE

<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	4,300.0
Species	Rat
<u>Acute toxicity - dermal</u>	
Notes (dermal LD₅₀)	LD ₅₀ >1700 mg/kg, Dermal, Rabbit
ATE dermal (mg/kg)	1,100.0
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC₅₀ vapours mg/l)	5,000.0
Species	Rat
ATE inhalation (gases ppm)	4,500.0
ATE inhalation (vapours mg/l)	11.0

Bijlard Spuitlijm (Transparent)

ATE inhalation
(dusts/mists mg/l) 1.5

CYCLOHEXANE

Acute toxicity - oral

Notes (oral LD₅₀) LC50 >5000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2000 mg/kg, Dermal, Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation
(LC₅₀ vapours mg/l) 32.88

Notes (inhalation LC₅₀) LC50 32.88 mg/l, Inhalation, Rat

ATE inhalation (vapours
mg/l) 32,880.0

Skin corrosion/irritation

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation

Serious eye
damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity -
fertility Based on available data the classification criteria are not met.

Reproductive toxicity -
development Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways.

Bijlard Spuitlijm (Transparent)

SECTION 12: Ecological information

Ecotoxicity Dangerous for the environment. May cause long lasting harmful effects to aquatic life.

Acute aquatic toxicity

Chronic aquatic toxicity

12.1. Toxicity

Toxicity The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment. Information given for the mixture in sect 3 is based upon the results of the calculation method. Some of the information given is also taken from data given for the individual ingredients of the mixture.

Acute aquatic toxicity

Acute toxicity - fish Not determined.

Acute toxicity - aquatic invertebrates Not determined.

Acute toxicity - aquatic plants Not determined.

Acute toxicity - microorganisms Not determined.

Acute toxicity - terrestrial Not determined.

Chronic aquatic toxicity

Chronic toxicity - fish early life stage Not determined.

Short term toxicity - embryo and sac fry stages Not determined.

Chronic toxicity - aquatic invertebrates Not determined.

Chronic toxicity in fish

Ecological information on ingredients.

BUTANONE

Acute aquatic toxicity

Acute toxicity - fish LC50, 48 hours: > 100 mg/l, *Leuciscus idus* (Golden orfe)

Acute toxicity - aquatic invertebrates EC50, 48 hours: >100 mg/l, *Daphnia magna*

Acute toxicity - aquatic plants EC50, 72 hours: >100 mg/l, *Pseudokirchneriella subcapitata*

Acute toxicity - microorganisms EC3, 16 hours: 1150 mg/l, Bacteria

ACETONE

Acute aquatic toxicity

Acute toxicity - fish LC50, 96 hours: 5540 mg/l, *Oncorhynchus mykiss* (Rainbow trout)
LC50, 96 hours: 11000 mg/l, *Alburnus alburnus* (bleak)

Bijlard Spuitlijm (Transparent)

Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 8800 mg/l, Daphnia pulex (water flea) EC ₅₀ , 24 hours: 2100 mg/l, Artemisia salina
Acute toxicity - aquatic plants	NOEC, 96 hours: 530 mg/l, Freshwater algae NOEC, 96 hours: 430 mg/l, Marinewater algae
Acute toxicity - microorganisms	EC ₁₂ , 30 minutes: 1000 mg/l, Activated sludge
Acute toxicity - terrestrial	LC ₅₀ , 48 hours: 0.1-1 mg/cm ³ , Eisenia Fetida (Earthworm) LD ₅₀ , 48 hours: 20000 mg/l, Ambystoma mexicanum LD ₅₀ , 48 hours: 24000 mg/l, Xenopus laevis

Chronic aquatic toxicity

Chronic toxicity - aquatic invertebrates	NOEC, 21 days: 0.1 mg/l, Daphnia magna
---	--

CYCLOHEXANE

Acute aquatic toxicity

LE(C)₅₀	0.1 < L(E)C ₅₀ ≤ 1
M factor (Acute)	1
Acute toxicity - fish	LC ₅₀ , 48 hours: 4.53 mg/l,
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 0.9 mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC ₅₀ , 72 hours: >4 mg/l, Selenastrum capricornutum

Chronic aquatic toxicity

NOEC	0.001 < NOEC ≤ 0.01
Degradability	Rapidly degradable
M factor (Chronic)	1

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Phototransformation Not relevant.

Stability (hydrolysis) Not determined.

Biodegradation Not determined.

Biological oxygen demand Not determined.

Chemical oxygen demand Not determined.

Ecological information on ingredients.

BUTANONE

Persistence and degradability	The product is biodegradable.
Biodegradation	>60% 28, days

Bijlard Spuitlijm (Transparent)

ACETONE

Persistence and degradability

The product is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

Ecological information on ingredients.

BUTANONE

Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

ACETONE

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

Adsorption/desorption coefficient Not determined.

Henry's law constant Not determined.

Surface tension Not determined.

Environmental distribution

Ecological information on ingredients.

BUTANONE

Mobility Not considered mobile.

ACETONE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. The product is water-soluble and may spread in water systems.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

BUTANONE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not known.

Bijlard Spuitlijm (Transparent)

Ecological information on ingredients.

ACETONE

Other adverse effects

WGK 1

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information

Waste is suitable for incineration. The generation of waste should be minimised or avoided wherever possible. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

Disposal methods

Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents.

Product

Uncleaned packaging

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1133

UN No. (IMDG) 1133

UN No. (ICAO) 1133

UN No. (ADN) 1133

14.2. UN proper shipping name

Proper shipping name (ADR/RID) ADHESIVES

Proper shipping name (IMDG) ADHESIVES (CONTAINS Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane, HEXANE-norm)

Proper shipping name (ICAO) ADHESIVES

Proper shipping name (ADN) ADHESIVES

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

Bijlard Spuitlijm (Transparent)

ADR/RID packing group	II
IMDG packing group	II
ICAO packing group	II
ADN packing group	II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-E, S-D
ADR transport category	2
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

Segregation Code

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Transport/Additional information Marine Pollutant Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Carriage of Dangerous Goods and use of Transportable Pressure Equipment Regulations 2009 as amended(SI 2009/1348) The Control of Substances Hazardous to Health Regulations 2002. (SI 2002 No 2677) as amended
EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 2015/830 of 28 May 2015.
Guidance	EH40/2005 Workplace exposure limits L131 Approved Classification and Labelling Guide (Sixth Edition)
Authorisations (Annex XIV Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Annex XVII Regulation 1907/2006)	No specific restrictions on use are known for this product.

Bijlard Spuitlijm (Transparent)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information	Only trained personnel should use this material.
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	27/11/2023
Revision	11
Supersedes date	27/11/2025
SDS status	Approved.
Hazard statements in full	H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. EUH208 Contains ROSIN. May produce an allergic reaction.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.