Version number 84 (replaces version 83) Printing date 28.07.2022 Revision: 30.03.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: BIJLARD CITRONEL SPUITBUS 500 ML
- · Article number: RB0018
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · **Product category** Flux agents for casting
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Cleaning agent/ Cleaner
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Bijlard International

Platinastraat 141

2718 SR Zoetermeer

The Netherlands

Tel: +31 79 343 7538

e-mail: info@bijlard.com

- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

Tel: +31 (0)79 343 75 38 (9.00 - 17.00)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

IRL: Beaumont Hospital - National Poisons Information Centre: Tel: +353 1 8092566

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Aerosol 1



environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



H315 Skin Irrit. 2 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

(Contd. on page 2)

Printing date 28.07.2022 Version number 84 (replaces version 83) Revision: 30.03.2022

Trade name: BIJLARD CITRONEL SPUITBUS 500 ML

(Contd. of page 1)

#### · 2.2 Label elements

#### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02

GHS07 GHS09

#### · Signal word Danger

#### · Hazard-determining components of labelling:

(R)-p-mentha-1,8-diene

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

*H410 Very toxic to aquatic life with long lasting effects.* 

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

*P211* Do not spray on an open flame or other ignition source.

*P251* Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

#### · Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

## SECTION 3: Composition/information on ingredients

#### · 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

| CAS: 5989-27-5             | (R)-p-mentha-1,8-diene  | 50-<75%   |
|----------------------------|---|-----------|
| EINECS: 227-813-5          | <b>◈</b> Flam. Liq. 3, H226                                   |           |
| Index number: 601-029-00-7 | <b>&amp;</b> Asp. Tox. 1, H304                                |           |
| Reg.nr.: 01-2119529223-47  | 🚯 Aquatic Acute 1, H400; Aquatic Chronic 1, H410              |           |
|                            | • Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 |           |
| CAS: 74-98-6               | propane   | 10-<12.5% |
| EINECS: 200-827-9          | <b>◈</b> Flam. Gas 1A, H220                                   |           |
| Index number: 601-003-00-5 | Press. Gas (Comp.), H280                                      |           |
| Reg.nr.: 01-2119486944-21  |   |           |
| CAS: 106-97-8              | butane (containing < 0,1 % butadiene (203-450-8))             | 5-<10%    |
| EINECS: 203-448-7          | <b>♠</b> Flam. Gas 1A, H220                                   |           |
| Index number: 601-004-00-0 | Press. Gas (Comp.), H280                                      |           |
| Reg.nr.: 01-2119474691-32  |   |           |
| CAS: 75-28-5               | isobutane (containing < 0,1 % butadiene (203-450-8))          | 5-<10%    |
| EINECS: 200-857-2          | <b>(A)</b> Flam. Gas 1A, H220                                 |           |
| Index number: 601-004-00-0 | Press. Gas (Comp.), H280                                      |           |
| Reg.nr.: 01-2119485395-27  |   |           |

page 3)

GB -

Printing date 28.07.2022 Version number 84 (replaces version 83) Revision: 30.03.2022

Trade name: BIJLARD CITRONEL SPUITBUS 500 ML

(Contd. of page 2)

| · Regulation (EC) No 648/2004 on detergents / Labelling for contents |            |
|--|------------|
| perfumes (Limonene)  | ≥30%       |
| aliphatic hydrocarbons   | ≥15 - <30% |

· Additional information: For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

No special measures required.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

(Contd. on page 4)

Printing date 28.07.2022 Version number 84 (replaces version 83) Revision: 30.03.2022

Trade name: BIJLARD CITRONEL SPUITBUS 500 ML

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· Hand protection



Protective gloves

#### · Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

#### · Penetration time of glove material

Butyl rubber gloves with a thickness of  $0.4\ mm$  are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42-480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

(Contd. on page 5)

Printing date 28.07.2022 Version number 84 (replaces version 83) Revision: 30.03.2022

Trade name: BIJLARD CITRONEL SPUITBUS 500 ML

· Eye/face protection Not required.

(Contd. of page 4)

### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Fruit-like
Odour threshold:
Melting point/freezing point:

Aerosol
Clear
Fruit-like
Not determined.
Undetermined.

· Boiling point or initial boiling point and boiling

range Not applicable, as aerosol.

· Flammability Not applicable.

· Lower and upper explosion limit

• Lower: 0.7 Vol % (5989-27-5 (R)-p-mentha-1,8-diene)

Upper: 10.9 Vol % (74-98-6 propane)
Flash point: Not applicable, as aerosol.

• Ignition temperature: 245 °C (473 °F) (5989-27-5 (R)-p-mentha-1,8-diene)

• Decomposition temperature: Not determined. • pH Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

• Vapour pressure at 20 °C (68 °F): 3500 hPa (2625.2 mm Hg)

· Density and/or relative density

Density at 20 °C (68 °F):
Relative density
Vapour density
Not determined.
Not determined.

· 9.2 Other information

· Appearance:

Form: Aerosol

· Important information on protection of health and

environment, and on safety.

• Explosive properties: Not determined.

· Solvent content:

• Organic solvents: 100.0 %
 • VOC (EC) -- • VOC-EU% 100.00 %

· VOC-EU% 100.00 % · Solids content: 0.0 %

· Change in condition

• Evaporation rate Not applicable.

· Information with regard to physical hazard classes

Explosives VoidFlammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised container:

May burst if heated.

Oxidising gases
Gases under pressure
Flammable liquids
Flammable solids
Self-reactive substances and mixtures

(Contd. on page 6)

Printing date 28.07.2022 Version number 84 (replaces version 83) Revision: 30.03.2022

Trade name: BIJLARD CITRONEL SPUITBUS 500 ML

|                      |      | (Contd. of page 5) |
|----------------------|------|--------------------|
| · Pyrophoric liquids | Void |                    |
| · Pyrophoric solids  | Void |                    |

· Pyr · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void Void · Corrosive to metals · Desensitised explosives Void

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity
- · LD/LC50 values relevant for classification:

### 5989-27-5 (R)-p-mentha-1,8-diene

 Oral
 LD50
 2000 mg/kg (rat)

 Dermal
 LD50
 >5000 mg/kg (rabbit)

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

#### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

#### 5989-27-5 (R)-p-mentha-1,8-diene

EC50/48 h 0.36 mg/l (daphnia magna)

EC50 / 72 h | 150 mg/l (algae)

EC50/72h 0.72 mg/l (fish)

LC50 / 72 h | 0.72 mg/l (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 7)

Printing date 28.07.2022 Version number 84 (replaces version 83) Revision: 30.03.2022

Trade name: BIJLARD CITRONEL SPUITBUS 500 ML

(Contd. of page 6)

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Very toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

| 14.1 UN number or ID number<br>ADR, IMDG, IATA | UN1950                                  |
|--|---|
| · 14.2 UN proper shipping name                 |   |
| ADR  | 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOU |
| · IMDG   | AEROSOLS, MARINE POLLUTANT              |
| · IATA   | AEROSOLS, flammable                     |
|  | 2 5F Gases.                             |
|  | 2.1                                     |
| · Class<br>· Label<br>· IMDG                   | 2.1                                     |

· IATA



· Class 2.1 Gases.

(Contd. on page 8)

Printing date 28.07.2022 Version number 84 (replaces version 83) Revision: 30.03.2022

Trade name: BIJLARD CITRONEL SPUITBUS 500 ML

|  | (Contd. of page  |
|--|--|
| Label  | 2.1  |
| 14.4 Packing group<br>ADR, IMDG, IATA  | not regulated  |
| 14.5 Environmental hazards:  |  |
| Marine pollutant:  | Yes  |
|  | Symbol (fish and tree)   |
| Special marking (ADR):   | Symbol (fish and tree)   |
| 14.6 Special precautions for user<br>Hazard identification number (Kemler code): | Warning: Gases.  |
| EMS Number:  | F- $D$ , $S$ - $U$   |
| Stowage Code   | SW1 Protected from sources of heat.  |
|  | SW22 For AEROSOLS with a maximum capacity of 1   |
|  | litre: Category A. For AEROSOLS with a capacity above  |
|  | 1 litre: Category B. For WASTE AEROSOLS: Category  |
|  | C, Clear of living quarters.   |
| Segregation Code   | SG69 For AEROSOLS with a maximum capacity of 1   |
|  | litre:   |
|  | Segregation as for class 9. Stow "separated from" class  |
|  | except for division 1.4.   |
|  | For AEROSOLS with a capacity above 1 litre:<br>Segregation as for the appropriate subdivision of class |
|  | For WASTE AEROSOLS:  |
|  | Segregation as for the appropriate subdivision of class  |
| 14.7 Maritime transport in bulk according to IM.                                 |  |
| instruments  | Not applicable.  |
| Transport/Additional information:  |  |
| ADR  |  |
| Limited quantities (LQ)  | 1L   |
| Excepted quantities (EQ)   | Code: E0   |
|  | Not permitted as Excepted Quantity   |
|  | Code: E0   |
|  | Not permitted as Excepted Quantity   |
| Transport category   | 2  |
| Tunnel restriction code  | D  |
| IMDG   |  |
| Limited quantities (LQ)  | 1L   |
| Excepted quantities (EQ)   | Code: E0   |
|  | Not permitted as Excepted Quantity   |
|  | Code: E0   |
|  |  |
|  | Not permitted as Excepted Quantity   |
| UN "Model Regulation":   | UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS   |

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- $\cdot \textit{Named dangerous substances ANNEX I} \ \textit{None of the ingredients is listed}.$
- · Seveso category

E1 Hazardous to the Aquatic Environment

P3a FLAMMABLE AEROSOLS

 $\cdot$  Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t

(Contd. on page 9)

Printing date 28.07.2022 Version number 84 (replaces version 83) Revision: 30.03.2022

Trade name: BIJLARD CITRONEL SPUITBUS 500 ML

(Contd. of page 8)

- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · LIST OF SUBSTANCES SUBJECT TO AUTHORISATION (UK ANNEX XIV)
- · Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

*H410* Very toxic to aquatic life with long lasting effects.

· Contact: QHSE Department

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Asp. Tox. 1: Aspiration hazard - Category 1

 $Aquatic\ Acute\ 1:\ Hazardous\ to\ the\ aquatic\ environment\ -\ acute\ aquatic\ hazard\ -\ Category\ 1$ 

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

 $\cdot$  \* Data compared to the previous version altered.

GB