

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Product name : Bijlard Spuitlijm 0023
UFI : NQX1-M079-3005-C8DD
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against**Relevant identified uses**

Main use category : Professional use, Industrial
Use of the substance/mixture : Sprayable contact adhesive

Title	Life cycle stage	Use descriptors
Bijlard Spuitlijm 0023	Industrial, Professional	SU19, PC1, PROC7

Full text of use descriptors: see section 16

1.3. Details of the supplier of the safety data sheet

Bijlard International
Platinastraat 141
2718 SR Zoetermeer
The Netherlands
T +31 (0) 79 343 75 38
info@bijlard.com, www.bijlard.com

1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 2 H225
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Single exposure, Category 3, H336
Narcosis
Hazardous to the aquatic environment – Chronic Hazard, H412
Category 3

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

Bijlard Spuitlijm 0023


Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: acetone; propan-2-one; propanone

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P233 - Keep container tightly closed.
P235 - Keep cool.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P403+P235 - Store in a well-ventilated place. Keep cool.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	acetone; propan-2-one; propanone (67-64-1), Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene (68610-51-5), Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	acetone; propan-2-one; propanone (67-64-1), Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene (68610-51-5), Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Product name	Product identifier	% w/w (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetone; propan-2-one; propanone	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-49	30 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
ethyl acetate substance with national workplace exposure limit(s) (GB)	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5 REACH-no: 01-2119475103-46	10 – 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Bijlard Spuitlijm 0023

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Product name	Product identifier	% w/w (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C6, isoalkanes, <5% n-hexane	EC-No.: 931-254-9 REACH-no: 01-2119484651-34	10 – 20	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	EC-No.: 927-510-4 REACH-no: 01-2119475515-33	5 – 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene	CAS-No.: 68610-51-5 EC-No.: 271-867-2 REACH-no: 01-2119496062-39	0.1 – 1	Repr. 1A, H360 Aquatic Chronic 4, H413

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: In case of doubt or persistent symptoms, consult always a physician. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical attention.
First-aid measures after skin contact	: Wash skin with mild soap and water. If skin irritation or rash occurs: Get medical advice/attention. Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse immediately with plenty of water, also under the eyelids. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists. Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Seek medical attention if ill effect develops. Call a poison center or a doctor if you feel unwell.
Self protection of the first-aiders	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: Irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Dry chemical, CO ₂ , or water spray or regular foam. Making extinguishing agents environment-friendly. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

Bijlard Spuitlijm 0023

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: No direct explosion hazard.
Reactivity in case of fire	: Combustion produces irritating gases.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Wear personal protective equipment. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	---

For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. Evacuate unnecessary personnel. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	: Take up liquid spill into absorbent material. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Bijlard Spuitlijm 0023

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Keep only in the original container in a cool, well-ventilated place. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Packaging materials	: Store always product in container of same material as original container.

7.3. Specific end use(s)

No supplementary information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

ethyl acetate (141-78-6)	
United Kingdom - Occupational Exposure Limits	
Local name	Ethyl acetate
WEL TWA (OEL TWA)	734 mg/m ³
	200 ppm
WEL STEL (OEL STEL)	1468 mg/m ³
	400 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Provide adequate ventilation. Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:

Safety glasses. Gloves. Protective clothing.

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Wear eye glasses with side protection according to EN 166. Safety glasses

Skin protection

Skin and body protection:

Wear suitable protective clothing. Choose protective clothing according to the type, quantity and concentration of hazardous substances, and the specific workplace. EN 13034

Hand protection:

Wear suitable gloves tested to EN374. Recommendation: Suitable chemical resistant safety gloves (EN 374) also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374): e.g. nitrile rubber (>=0.4 mm), butyl rubber (>=0.7 mm) and others. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Bijlard Spuitlijm 0023

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Respiratory protection

Respiratory protection:

In the event of exposure to high concentrations of dust or vapour: Use mask type P1 (EN 143 EU) against interfering environmental influences. For higher levels of protection, use mask filter type ABEK-P2 (EU EN 143). Breathing equipment and components have to be tested and approved under appropriate government standards such as CEN (EU). . May cause drowsiness or dizziness.

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

If on skin, take off contaminated clothing. Keep away from food, drink and animal feedingstuffs. Avoid contact with skin and eyes. Wash hands before breaks and after work.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: transparent. Yellow.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: > 35 °C
Flammability	: Highly flammable liquid and vapour.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: < 23 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 24.39 – 60.976 mm ² /s
Viscosity, dynamic	: 20 – 50 mPa·s
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 0.82 kg/l
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

Other safety characteristics

VOC content : ≈ 70 %

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Highly flammable liquid and vapour.

10.2. Chemical stability

Stable in use and storage conditions as recommended in item 7.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

Bijlard Spuitlijm 0023

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

acetone; propan-2-one; propanone (67-64-1)

LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	7426 – 15800 mg/kg
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
ATE oral	5800 mg/kg bodyweight
ATE dermal	7426 mg/kg bodyweight

Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene (68610-51-5)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: EPA OPP 81-1 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

ethyl acetate (141-78-6)

LD50 oral rat	11.3 ml/kg
LD50 dermal rat	20000 mg/kg
LD50 dermal rabbit	20000 mg/kg bodyweight Animal: rabbit, Animal sex: male
ATE dermal	20000 mg/kg bodyweight

Hydrocarbons, C6, isoalkanes, <5% n-hexane

LD50 oral rat	25 mg/kg bodyweight
LD50 dermal rabbit	5 mg/kg bodyweight
LC50 Inhalation - Rat [ppm]	73860 ppm/4h

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

LD50 oral rat	8 ml/kg
LD50 dermal rat	2800 – 3100 mg/kg bodyweight Animal: rat, Remarks on results: other:
LC50 Inhalation - Rat	17.3 – 23.3 mg/l
LC50 Inhalation - Rat [ppm]	4240 – 4450 ppm
ATE dermal	2800 mg/kg bodyweight

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.

Bijlard Spuitlijm 0023

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified

acetone; propan-2-one; propanone (67-64-1)

LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male

STOT-single exposure : May cause drowsiness or dizziness.

acetone; propan-2-one; propanone (67-64-1)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

ethyl acetate (141-78-6)

LOAEL (oral, rat)	3600 mg/kg bodyweight
NOAEL (oral, rat)	900 mg/kg bodyweight
STOT-single exposure	May cause drowsiness or dizziness.

Hydrocarbons, C6, isoalkanes, <5% n-hexane

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Not classified

ethyl acetate (141-78-6)

LOAEL (oral, rat, 90 days)	3600 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
NOAEL (oral, rat, 90 days)	900 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

NOAEC (inhalation, rat, vapour, 90 days)	3.3 mg/l air Animal: rat, Animal sex: male
--	--

Aspiration hazard : Not classified

Bijlard Spuitlijm 0023

Viscosity, kinematic	24.39 – 60.976 mm²/s
----------------------	----------------------

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Viscosity, kinematic	0.46 mm²/s
----------------------	------------

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Viscosity, kinematic	0.67 mm²/s
----------------------	------------

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified

Bijlard Spuitlijm 0023

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous to the aquatic environment, long-term : Harmful to aquatic life with long lasting effects.
(chronic)

acetone; propan-2-one; propanone (67-64-1)	
LC50 - Fish [1]	5.54 – 8.12 g/l
EC50 - Crustacea [1]	8.8 g/l
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene (68610-51-5)	
LC50 - Fish [1]	> 0.2 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 0.2 mg/l Test organisms (species): Daphnia magna

ethyl acetate (141-78-6)	
LC50 - Fish [1]	230 mg/l
NOEC (acute)	> 9.65 mg/l (32d)
NOEC (chronic)	2.4 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	9.65 mg/l (32 d)
NOEC chronic crustacea	2.4 mg/l (21 d)

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	
LC50 - Fish [1]	110 µg/l
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	170 µg/L (21 d)

12.2. Persistence and degradability

Bijlard Spuitlijm 0023	
Persistence and degradability	Rapidly degradable
acetone; propan-2-one; propanone (67-64-1)	
Persistence and degradability	Rapidly degradable
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene (68610-51-5)	
Persistence and degradability	Rapidly degradable
ethyl acetate (141-78-6)	
Persistence and degradability	Rapidly degradable
Biodegradation	> 70 % OECD 301 D;MSDS Ethylacetat, Sasol
Hydrocarbons, C6, isoalkanes, <5% n-hexane	
Persistence and degradability	Rapidly degradable
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	
Persistence and degradability	Rapidly degradable
Biodegradation	98 % OECD 301 F;28 d;SDS Heptan, Chemark

Bijlard Spuitlijm 0023

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.3. Bioaccumulative potential

acetone; propan-2-one; propanone (67-64-1)

Partition coefficient n-octanol/water (Log Pow)	-0.24 – -0.23
---	---------------

Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene (68610-51-5)

Partition coefficient n-octanol/water (Log Pow)	7.17 – 8.17
---	-------------

ethyl acetate (141-78-6)

Partition coefficient n-octanol/water (Log Pow)	0.68 – 0.73 @ 20 - 25 °C
---	--------------------------

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Partition coefficient n-octanol/water (Log Pow)	3.42 – 5.8 @ 20 °C and pH 7
---	-----------------------------

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Partition coefficient n-octanol/water (Log Pow)	3.07 – 3.78 @ 20 °C and pH 7
---	------------------------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component

Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	acetone; propan-2-one; propanone (67-64-1), Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene (68610-51-5), Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
--	--

Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	acetone; propan-2-one; propanone (67-64-1), Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene (68610-51-5), Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
---	--

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Bijlard Spuitlijm 0023

Other information	Avoid release to the environment.
-------------------	-----------------------------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Disposal must be done according to official regulations.
Additional information	: Flammable vapours may accumulate in the container. Do not re-use empty containers.
Ecological waste information	: Avoid release to the environment.
European List of Waste (LoW, EC 2000/532)	: 20 01 13* - solvents

Bijlard Spuitlijm 0023

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

HP Code

: HP3 - "Flammable:"
– flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
– flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
– flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
– flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
– water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
– other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.
HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1133	UN 1133	UN 1133	UN 1133	UN 1133
14.2. UN proper shipping name				
ADHESIVES	ADHESIVES	Adhesives	ADHESIVES	ADHESIVES
Transport document description				
UN 1133 ADHESIVES, 3, I, (D/E)	UN 1133 ADHESIVES, 3, I	UN 1133 Adhesives, 3, I	UN 1133 ADHESIVES, 3, I	UN 1133 ADHESIVES, 3, I
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
I	I	I	I	I
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-E EmS-No. (Spillage): S-D	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available.				

14.6. Special precautions for user

Overland transport


Classification code (ADR) : F1
Limited quantities (ADR) : 500ml
Excepted quantities (ADR) : E3
Packing instructions (ADR) : P001
Mixed packing provisions (ADR) : MP7, MP17

Bijlard Spuitlijm 0023

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Portable tank and bulk container instructions (ADR)	: T11
Portable tank and bulk container special provisions (ADR)	: TP1, TP8, TP27
Tank code (ADR)	: L4BN
Vehicle for tank carriage	: FL
Transport category (ADR)	: 1
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

Transport by sea

Limited quantities (IMDG)	: 500 ml
Excepted quantities (IMDG)	: E3
Packing instructions (IMDG)	: P001
Tank instructions (IMDG)	: T11
Tank special provisions (IMDG)	: TP1, TP8, TP27
Stowage category (IMDG)	: E
Properties and observations (IMDG)	: Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with water depends upon their composition.

Air transport

PCA Excepted quantities (IATA)	: E3
PCA Limited quantities (IATA)	: Forbidden
PCA limited quantity max net quantity (IATA)	: Forbidden
PCA packing instructions (IATA)	: 351
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 361
CAO max net quantity (IATA)	: 30L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

Inland waterway transport

Classification code (ADN)	: F1
Limited quantities (ADN)	: 500 ml
Excepted quantities (ADN)	: E3
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1

Rail transport

Classification code (RID)	: F1
Limited quantities (RID)	: 500ml
Excepted quantities (RID)	: E3
Packing instructions (RID)	: P001
Mixed packing provisions (RID)	: MP7, MP17
Portable tank and bulk container instructions (RID)	: T11
Portable tank and bulk container special provisions (RID)	: TP1, TP8, TP27
Tank codes for RID tanks (RID)	: L4BN
Transport category (RID)	: 1
Hazard identification number (RID)	: 33

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Bijlard Spuitlijm 0023

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	acetone; propan-2-one; propanone ; ethyl acetate ; Hydrocarbons, C6, isoalkanes, <5% n-hexane ; Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(a)	acetone; propan-2-one; propanone ; ethyl acetate ; Hydrocarbons, C6, isoalkanes, <5% n-hexane ; Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(c)	Hydrocarbons, C6, isoalkanes, <5% n-hexane ; Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

Organic solvent : Yes
VOC content : ≈ 70 %

Explosives Precursors Regulation (EU 2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Bijlard Spuitlijm 0023

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Drug Precursors Regulation (EC 273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

15.2. Chemical safety assessment

No chemical safety assessment has been carried out for the substance or the mixture by the supplier

A chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DNEL	Derived-No Effect Level
EC50	Median effective concentration
LC50	Median lethal concentration
LD50	Median lethal dose
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
STP	Sewage treatment plant
vPvB	Very Persistent and Very Bioaccumulative
ACGIH	American Conference of Government Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS-No.	Chemical Abstract Service number
COD	Chemical oxygen demand (COD)
CSA	Chemical safety assessment
DMEL	Derived Minimal Effect level
EC-No.	European Community number
ED	Endocrine disruptor
EN	European Standard
EWC	European waste catalogue
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LOAEL	Lowest Observed Adverse Effect Level

Bijlard Spuitlijm 0023

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

Log Kow	Partition coefficient n-octanol/water (Log Kow)
Log Pow	Partition coefficient n-octanol/water (Log Pow)
MAK	maximum workplace concentration
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
OSHA	Occupational Safety Health Administration
PPE	Personal protection equipment
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
TF	Technical function
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TWA	Time Weighted Average
VOC	Volatile Organic Compounds
UFI	Unique Formula Identifier

Other information

: **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Repr. 1A	Reproductive toxicity, Category 1A
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

Bijlard Spuitlijm 0023

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:

H336	May cause drowsiness or dizziness.
H360	May damage fertility or the unborn child.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Full text of use descriptors

PC1	Adhesives, sealants
PROC7	Industrial spraying
SU19	Building and construction work

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 2	H225	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 3	H412	Calculation method

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.