



## SAFETY DATA SHEET BIJLARD SPUITLIJM 2514R

According to Regulation (EC) No 1907/2006, Annex II, as amended.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name                   BIJLARD SPUITLIJM 2514R  
Product number                F4597/1

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses                 Adhesive  
Uses advised against         Applications involving the use of naked flames and static discharges Non-industrial, non-professional uses.

#### 1.3. Details of the supplier of the safety data sheet

Supplier                         Bijlard International  
                                      Platinastraat 141  
                                      2718 SR Zoetermeer  
                                      The Netherlands  
                                      +31 79 343 7538  
                                      +31 79 343 7539  
                                      info@bijlard.com

#### 1.4. Emergency telephone number

Emergency telephone         +31 (0) 79-3437538

### SECTION 2: Hazards identification


#### 2.1. Classification of the substance or mixture

##### Classification (EC 1272/2008)

Physical hazards               Flam. Liq. 2 - H225  
Health hazards                 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373  
Environmental hazards       Aquatic Chronic 2 - H411

#### 2.2. Label elements

##### Hazard pictograms



Signal word

Danger

## BIJLARD SPUITLIJM 2514R

<b>Hazard statements</b>	<p>EUH208 Contains ROSIN. May produce an allergic reaction.</p> <p>H225 Highly flammable liquid and vapour.</p> <p>H315 Causes skin irritation.</p> <p>H319 Causes serious eye irritation.</p> <p>H361d Suspected of damaging the unborn child.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H373 May cause damage to organs through prolonged or repeated exposure.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p>
<b>Precautionary statements</b>	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P243 Take action to prevent static discharges.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves, eye and face protection.</p> <p>P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p>
<b>Contains</b>	Hydrocarbons, C6-C7,n-alkanes, isoalkanes,cyclics, <5% n-hexane, BUTANONE, TOLUENE, acetone
<b>Supplementary precautionary statements</b>	<p>P242 Use non-sparking tools.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P308+P313 IF exposed or concerned: Get medical advice/ attention.</p> <p>P404 Store in a closed container.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>Hydrocarbons, C6-C7,n-alkanes, isoalkanes,cyclics, &lt;5% n-hexane</b>	<b>40-50%</b>
CAS number: —	EC number: 921-024-6
	REACH registration number: 01-2119475514-35
<b>Classification</b>	
Flam. Liq. 2 - H225	
Skin Irrit. 2 - H315	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	
Aquatic Chronic 2 - H411	

**BIJLARD SPUITLIJM 2514R**

<b>BUTANONE</b>			<b>20-30%</b>
CAS number: 78-93-3	EC number: 201-159-0	REACH registration number: 01-2119457290-43-XXXX	
<b>Classification</b>			
Flam. Liq. 2 - H225			
Eye Irrit. 2 - H319			
STOT SE 3 - H336			
<b>TOLUENE</b>			<b>10-20%</b>
CAS number: 108-88-3	EC number: 203-625-9	REACH registration number: 01-21194713110-51	
<b>Classification</b>			
Flam. Liq. 2 - H225			
Skin Irrit. 2 - H315			
Repr. 2 - H361d			
STOT SE 3 - H336			
STOT RE 2 - H373			
Asp. Tox. 1 - H304			
<b>ACETONE</b>			<b>7-10%</b>
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49-XXXX	
<b>Classification</b>			
Flam. Liq. 2 - H225			
Eye Irrit. 2 - H319			
STOT SE 3 - H336			
<b>ROSIN</b>			<b>&lt;1.0%</b>
CAS number: 8050-09-7	EC number: 232-475-7	REACH registration number: 01-2119480418-32-XXXX	
<b>Classification</b>			
Skin Sens. 1 - H317			
<b>Magnesium Oxide</b>			<b>&lt;1.0%</b>
CAS number: 1309-48-4	EC number: 215-171-9		
<b>Classification</b>			
Not Classified			

**BIJLARD SPUITLIJM 2514R**

<b>Zinc Oxide</b>			<b>&lt;1.0%</b>
CAS number: 1314-13-2	EC number: 215-222-5		
M factor (Acute) = 1	M factor (Chronic) = 1		
<b>Classification</b>			
Aquatic Acute 1 - H400			
Aquatic Chronic 1 - H410			
<b>Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene</b>			<b>&lt;1.0%</b>
CAS number: 68610-51-5	EC number: 271-867-2	REACH registration number: 01-2119496062-39-0000	
<b>Classification</b>			
Repr. 2 - H361d			
Aquatic Chronic 4 - H413			
<b>Talc</b>			<b>&lt;1.0%</b>
CAS number: 14807-96-6	EC number: 238-877-9		
<b>Classification</b>			
Acute Tox. 4 - H332			
STOT SE 3 - H335			

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**Composition comments** The data shown are in accordance with the latest EC Directives.

**Ingredient notes** This product contains ingredients which are subject to restriction according to ANNEX XVII of REACH, see section 15 for further details.

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

<b>General information</b>	Remove affected person from source of contamination. Remove contaminated soaked clothing immediately and dispose of safely
<b>Inhalation</b>	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
<b>Ingestion</b>	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if any discomfort continues.
<b>Skin contact</b>	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

##### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	Chemical burns must be treated by a physician. Get medical attention immediately.
<b>Inhalation</b>	Vapours may cause headache, fatigue, dizziness and nausea.
<b>Ingestion</b>	May cause stomach pain or vomiting.

## BIJLARD SPUITLIJM 2514R

**Skin contact** Prolonged contact may cause redness, irritation and dry skin.

**Eye contact** May cause temporary eye irritation.

### **4.3. Indication of any immediate medical attention and special treatment needed**

**Notes for the doctor** No specific recommendations. If in doubt, get medical attention promptly.

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

**Suitable extinguishing media** Carbon dioxide (CO<sub>2</sub>). Alcohol-resistant foam. Powder. Water spray, fog or mist.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

### **5.2. Special hazards arising from the substance or mixture**

**Specific hazards** No unusual fire or explosion hazards noted.

**Hazardous combustion products** When heated, vapours/gases hazardous to health may be formed.

### **5.3. Advice for firefighters**

**Protective actions during firefighting** Move containers from fire area if it can be done without risk. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

**Special protective equipment for firefighters** Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Eliminate all sources of ignition. Avoid inhalation of vapours and contact with skin and eyes. Take precautionary measures against static discharges. This product is a sprayable product and if applied in in such away, appropriate PPE and engineering measures should be taken to protect operators from the vapours, mists, aerosols, droplets, fume, gas, spray

### **6.2. Environmental precautions**

**Environmental precautions** Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. Do not discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment.

### **6.3. Methods and material for containment and cleaning up**

**Methods for cleaning up** Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water.

### **6.4. Reference to other sections**

**Reference to other sections** Wear protective clothing as described in Section 8 of this safety data sheet. Collect and dispose of spillage as indicated in Section 13.

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

**Usage precautions** Avoid spilling. Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

## BIJLARD SPUITLIJM 2514R

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep away from heat, sparks and open flame. Protect from freezing and direct sunlight. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store in tightly-closed, original container.

**Storage class** Flammable liquid storage.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

**Usage description** Contact with skin and eyes and inhalation of vapours must be avoided under all circumstances. This product is a sprayable product and if applied in in such away, appropriate PPE and engineering measures should be taken to protect operators from the vapours,mists,aerosols,droplets,fume,gas,spray

## SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### **BUTANONE**

Long-term exposure limit (8-hour TWA): 200 600

Short-term exposure limit (15-minute): 300 899

Sk

##### **TOLUENE**

Long-term exposure limit (8-hour TWA): WEL 50 ppm 191 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 100 ppm 384 mg/m<sup>3</sup>

Sk

##### **ACETONE**

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

##### **ROSIN**

Long-term exposure limit (8-hour TWA): WEL 0,05 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 0,15 mg/m<sup>3</sup>

Sen

##### **Magnesium Oxide**

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL

##### **Talc**

Long-term exposure limit (8-hour TWA): WEL 1 mg/m<sup>3</sup> respirable dust

Long-term exposure limit (8-hour TWA): WEL 1 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

Sk = Can be absorbed through skin.

Sk = Can be absorbed through the skin.

Sen = Capable of causing occupational asthma.

**Ingredient comments** WEL = Workplace Exposure Limits

Hydrocarbons, C6-C7,n-alkanes, isoalkanes,cyclics, <5% n-hexane

**BIJLARD SPUITLIJM 2514R**

<b>DNEL</b>	Consumer - Oral; Long term systemic effects: 699 mg/kg/day
	Industry - Oral; Long term systemic effects: 2035 mg/kg/day
	Consumer - Dermal; Long term systemic effects: 699 mg/kg/day
	Industry - Dermal; Long term systemic effects: 773 mg/kg/day
	Consumer - Inhalation; Long term systemic effects: 608 mg/m <sup>3</sup>

**BUTANONE (CAS: 78-93-3)**

<b>DNEL</b>	Industry - Inhalation; Short term local effects: 600 mg/kg/day
	Industry - Dermal; : 1161 mg/kg/day
	Consumer - Dermal; : 412 mg/kg/day
	Consumer - Inhalation; : 106 mg/m <sup>3</sup>

<b>PNEC</b>	- Fresh water; 55.8 mg/l
	- Sediment; 284.74 mg/kg
	- Soil; 22.5 mg/kg

**ACETONE (CAS: 67-64-1)**

<b>DNEL</b>	Industry - Dermal; Long term : 186 mg/kg/day
	Industry - Inhalation; Short term : 2420 mg/m <sup>3</sup>
	Industry - Inhalation; Long term : 1210 mg/m <sup>3</sup>
	Consumer - Oral; Long term : 62 mg/kg/day
	Consumer - Dermal; Long term : 62 mg/kg/day
	Consumer - Inhalation; Long term : 200 mg/m <sup>3</sup>

<b>PNEC</b>	- Fresh water; 10.6 mg/l
	- marine water; 1.06 mg/l
	- Intermittent release; 21 mg/l
	- Sediment (Freshwater); 30.4 mg/kg
	- Sediment (Marinewater); 3.04 mg/kg
	- STP; 100 mg/l
	- Soil; 29.5 mg/kg

**Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene (CAS: 68610-51-5)**

<b>DNEL</b>	Workers - Inhalation; Long term systemic effects: 0.29 mg/m <sup>3</sup>
	Workers - Dermal; Long term systemic effects: 0.42 mg/kg/day

<b>PNEC</b>	- Fresh water; 0.01 mg/l
	- marine water; 0.002 mg/l
	- Sediment (Freshwater); 426.6 mg/kg
	- Sediment (Marinewater); 85.25 mg/kg
	- STP; 100 mg/l
- ;	

**8.2. Exposure controls****Protective equipment****Appropriate engineering controls**

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. Dust may form explosive mixture with air. Take precautionary measures against static discharges.

## BIJLARD SPUITLIJM 2514R

<b>Eye/face protection</b>	The following protection should be worn: Chemical splash goggles.
<b>Hand protection</b>	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.
<b>Other skin and body protection</b>	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear apron or protective clothing in case of contact.
<b>Hygiene measures</b>	Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station. Provide eyewash station and safety shower. Wash contaminated clothing before reuse. Use appropriate skin cream to prevent drying of skin. Wash promptly if skin becomes contaminated. Change work clothing daily before leaving workplace.
<b>Respiratory protection</b>	If ventilation is inadequate, suitable respiratory protection must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P3.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Liquid.
<b>Colour</b>	Red.
<b>Odour</b>	Characteristic.
<b>Odour threshold</b>	Not available. Not available.
<b>pH</b>	Not available. Not determined.
<b>Melting point</b>	Not available.
<b>Initial boiling point and range</b>	80°C @
<b>Flash point</b>	-20°C
<b>Evaporation rate</b>	MODERATE
<b>Evaporation factor</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	No information available.
<b>Other flammability</b>	No information available.
<b>Vapour pressure</b>	Not available.
<b>Vapour density</b>	Not available.
<b>Relative density</b>	0.82 @ °C
<b>Bulk density</b>	Not available.
<b>Solubility(ies)</b>	Not available. Insoluble in water. Soluble in the following materials: Organic solvents.
<b>Partition coefficient</b>	Not available.
<b>Auto-ignition temperature</b>	Not determined.
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Non-viscous @ °C
<b>Explosive properties</b>	No information available.



## BIJLARD SPUITLIJM 2514R

**Comments** Information given is applicable to the product as supplied. Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.

**Density**

### 9.2. Other information

**Refractive index** Not applicable.

**Particle size** Not available.

**Molecular weight** Not applicable.

**Volatility** Not available.

**Critical temperature** Not available.

**Solvent content:**

**Volatile organic compound** Not available.

**Solids content:**

**Water:**

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** There are no known reactivity hazards associated with this product.

### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures and when used as recommended.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** No potentially hazardous reactions known.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition.

### 10.5. Incompatible materials

**Materials to avoid** Strong oxidising agents.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Does not decompose when used and stored as recommended. Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. When heated, vapours/gases hazardous to health may be formed.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Toxicological effects** Information given below for the mixture is based upon the results of the calculation method. Some of the information given is also taken from data given for the individual ingredients of the mixture.

#### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** Not determined.

#### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** Not determined.

## BIJLARD SPUITLIJM 2514R

### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** Not determined.

### Skin corrosion/irritation

**Skin corrosion/irritation** Based on available data the classification criteria are not met.

### Serious eye damage/irritation

**Serious eye damage/irritation** Causes eye irritation.

### Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

### Skin sensitisation

**Skin sensitisation** May cause sensitisation by skin contact.

### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

**Genotoxicity - in vivo** Based on available data the classification criteria are not met.

### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Reproductive toxicity - development** Based on available data the classification criteria are not met.

### Specific target organ toxicity - single exposure

**STOT - single exposure** May cause drowsiness or dizziness.

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Based on available data the classification criteria are not met.

### Aspiration hazard

**Aspiration hazard** Based on available data the classification criteria are not met.

### **General information**

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

### **Inhalation**

Vapour from this product may be hazardous by inhalation. Vapours may cause headache, fatigue, dizziness and nausea.

### **Ingestion**

Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

### **Skin contact**

Prolonged contact may cause dryness of the skin. Repeated exposure may cause skin dryness or cracking. Irritating to skin.

### **Eye contact**

Irritating to eyes.

### **Acute and chronic health hazards**

Prolonged contact may cause redness, irritation and dry skin. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis and skin cancer. Prolonged or repeated exposure to vapours in high concentrations may cause the following adverse effects: Central and/or peripheral nervous system damage. Brain damage.

### **Route of exposure**

Ingestion. Inhalation Skin and/or eye contact

### **Target organs**

Brain Respiratory system, lungs Mucous membranes Skin

## BIJLARD SPUITLIJM 2514R

<b>Medical symptoms</b>	Skin irritation. Irritation of eyes and mucous membranes. Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting.
<b>Medical considerations</b>	Skin disorders and allergies. Convulsions. Central nervous system depression. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

### SECTION 12: Ecological information

<b>Ecotoxicity</b>	The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.
<b><u>12.1. Toxicity</u></b>	
<b>Toxicity</b>	The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment. Information given below for the mixture is based upon the results of the calculation method. Some of the information given is also taken from data given for the individual ingredients of the mixture.
<b><u>Acute aquatic toxicity</u></b>	
<b>Acute toxicity - fish</b>	Not determined.
<b>Acute toxicity - aquatic invertebrates</b>	Not determined.
<b>Acute toxicity - aquatic plants</b>	Not determined.
<b>Acute toxicity - microorganisms</b>	Not determined.
<b>Acute toxicity - terrestrial</b>	Not determined.
<b><u>Chronic aquatic toxicity</u></b>	
<b>Chronic toxicity - fish early life stage</b>	Not determined.
<b>Short term toxicity - embryo and sac fry stages</b>	Not determined.
<b>Chronic toxicity - aquatic invertebrates</b>	Not determined.
<b><u>12.2. Persistence and degradability</u></b>	
<b>Persistence and degradability</b>	There are no data on the degradability of this product.
<b>Phototransformation</b>	Not relevant.
<b>Stability (hydrolysis)</b>	Not determined.
<b>Biodegradation</b>	Not determined.
<b>Biological oxygen demand</b>	Not determined.
<b>Chemical oxygen demand</b>	Not determined.
<b>Effect on Effluent Treatment</b>	
<b><u>12.3. Bioaccumulative potential</u></b>	
<b>Bioaccumulative potential</b>	No data available on bioaccumulation.
<b>Partition coefficient</b>	Not available.

## BIJLARD SPUITLIJM 2514R

### 12.4. Mobility in soil

<b>Mobility</b>	The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
<b>Adsorption/desorption coefficient</b>	Not determined.
<b>Henry's law constant</b>	Not determined.
<b>Surface tension</b>	Not determined.

### 12.5. Results of PBT and vPvB assessment

<b>Results of PBT and vPvB assessment</b>	This product does not contain any substances classified as PBT or vPvB.
---	---

### 12.6. Other adverse effects

<b>Other adverse effects</b>	Not known.
------------------------------	------------

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>General information</b>	Waste is suitable for incineration. The generation of waste should be minimised or avoided wherever possible. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.
<b>Disposal methods</b>	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents.

## SECTION 14: Transport information

<b>General</b>	Wear protective clothing as described in Section 8 of this safety data sheet.
<b>Road transport notes</b>	Avoid releasing into the environment.
<b>Rail transport notes</b>	Avoid releasing into the environment.
<b>Sea transport notes</b>	Do not release into the environment.

### 14.1. UN number

<b>UN No. (ADR/RID)</b>	1133
<b>UN No. (IMDG)</b>	1133

### 14.2. UN proper shipping name

<b>Proper shipping name (ADR/RID)</b>	ADHESIVES (Hydrocarbons, C6-C7,n-alkanes, isoalkanes,cyclic, <5% n-hexane)
<b>Proper shipping name (IMDG)</b>	ADHESIVES

### 14.3. Transport hazard class(es)

<b>ADR/RID class</b>	3
<b>ADR/RID label</b>	3
<b>IMDG class</b>	3

## BIJLARD SPUITLIJM 2514R

### Transport labels



#### 14.4. Packing group

IMDG packing group II

ICAO packing group II

#### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



#### 14.6. Special precautions for user

EmS F-E, S-D

Emergency Action Code •3YE

Hazard Identification Number (ADR/RID) 33

Tunnel restriction code (D/E)

Segregation Code

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Transport/Additional information Marine Pollutant Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>National regulations</b>	The Carriage of Dangerous Goods and use of Transportable Pressure Equipment Regulations 2009 as amended (SI 2009/1348) The Control of Substances Hazardous to Health Regulations 2002. (SI 2002 No 2677) as amended
<b>EU legislation</b>	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 2015/830 of 28 May 2015.
<b>Guidance</b>	EH40/2005 Workplace exposure limits L131 Approved Classification and Labelling Guide (Sixth Edition)
<b>Authorisations (Annex XIV Regulation 1907/2006)</b>	No specific authorisations are known for this product.

## BIJLARD SPUITLIJM 2514R

### Restrictions (Annex XVII Regulation 1907/2006)

This product contains Toluene which is listed in Entry 48 Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

<b>General information</b>	Only trained personnel should use this material.
<b>Revision comments</b>	NOTE: Lines within the margin indicate significant changes from the previous revision.
<b>Revision date</b>	11/02/2020
<b>Revision</b>	9
<b>Supersedes date</b>	19/09/2019
<b>SDS status</b>	Approved.
<b>Hazard statements in full</b>	<p>H225 Highly flammable liquid and vapour.  H304 May be fatal if swallowed and enters airways.  H315 Causes skin irritation.  H317 May cause an allergic skin reaction.  H319 Causes serious eye irritation.  H332 Harmful if inhaled.  H335 May cause respiratory irritation.  H336 May cause drowsiness or dizziness.  H361d Suspected of damaging the unborn child.  H373 May cause damage to organs through prolonged or repeated exposure.  H400 Very toxic to aquatic life.  H410 Very toxic to aquatic life with long lasting effects.  H411 Toxic to aquatic life with long lasting effects.  H413 May cause long lasting harmful effects to aquatic life.  EUH208 Contains ROSIN. May produce an allergic reaction.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.