



SAFETY DATA SHEET

BIJLARD GIETLIJM 2921 R

According to Regulation (EC) No 1907/2006, Annex II, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	BIJLARD GIETLIJM 2921 R
Product number	600000151
Synonyms; trade names	BIJLARD 2921 CURTAIN COATER ADHESIVE
UFI	UFI: NKAARW9Q-1J56-MK08

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Adhesive.
Uses advised against	Applications involving the use of naked flames and static discharges Non-industrial, non-professional uses.

1.3. Details of the supplier of the safety data sheet

Supplier	Bijlard International Platinastraat 141 2718 SR Zoetermeer The Netherlands +31 79 343 7538 +31 79 343 7539 info@bijlard.com
----------	---

1.4. Emergency telephone number

Emergency telephone	+31 (0) 79-3437538
---------------------	--------------------

SECTION 2: Hazards identification


2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Flam. Liq. 2 - H225
Health hazards	Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373
Environmental hazards	Aquatic Chronic 2 - H411

2.2. Label elements

Hazard pictograms



Signal word

Danger

BIJLARD GIETLIJM 2921 R

Hazard statements	<p>EUH208 Contains ROSIN. May produce an allergic reaction.</p> <p>H225 Highly flammable liquid and vapour.</p> <p>H315 Causes skin irritation.</p> <p>H319 Causes serious eye irritation.</p> <p>H361d Suspected of damaging the unborn child.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H373 May cause damage to organs through prolonged or repeated exposure.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p>
Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P242 Use non-sparking tools.</p> <p>P243 Take action to prevent static discharges.</p> <p>P260 Do not breathe vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P314 Get medical advice/ attention if you feel unwell.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
Contains	Hydrocarbons, C6-C7,n-alkanes, isoalkanes,cyclics, <5% n-hexane, BUTANONE, TOLUENE

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.1. Substances

Content

3.2. Mixtures

Hydrocarbons, C6-C7,n-alkanes, isoalkanes,cyclics, <5% n-hexane	30-40%
CAS number: —	EC number: 921-024-6
	REACH registration number: 01-2119475514-35
Classification	
Flam. Liq. 2 - H225	
Skin Irrit. 2 - H315	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	
Aquatic Chronic 2 - H411	

BIJLARD GIETLIJM 2921 R

BUTANONE 20-30%		
CAS number: 78-93-3	EC number: 201-159-0	REACH registration number: 01-2119457290-43-XXXX
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336		
TOLUENE 20-30%		
CAS number: 108-88-3	EC number: 203-625-9	REACH registration number: 01-2119471310-51-XXXX
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412		
ROSIN <1.0%		
CAS number: 8050-09-7	EC number: 232-475-7	REACH registration number: 01-2119480418-32-XXXX
Classification Skin Sens. 1 - H317		
Zinc Oxide <1.0%		
CAS number: 1314-13-2	EC number: 215-222-5	
M factor (Acute) = 1	M factor (Chronic) = 1	
Classification Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410		
XYLENE <1.0%		
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-XXXX
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315		

BIJLARD GIETLIJM 2921 R

ethylbenzene		<0.1%
CAS number: 100-41-4	EC number: 202-849-4	REACH registration number: 01-2119489370-35-XXXX
Classification		
Flam. Liq. 3 - H226		
Acute Tox. 4 - H312		
Acute Tox. 4 - H332		
STOT RE 2 - H373		
Asp. Tox. 1 - H304		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

Ingredient notes This product contains ingredients which are subject to restriction according to ANNEX XVII of REACH, see section 15 for further details.
As of February 2026, n-Hexane has been designated as an SVHC in the EU. [Although not directly added to the formulation, this substance is a constituent of a Hydrocarbon solvent in the formulation.]

SECTION 4: First aid measures**4.1. Description of first aid measures**

General information	Remove affected person from source of contamination. Remove contaminated soaked clothing immediately and dispose of safely
Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if any discomfort continues.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information	Chemical burns must be treated by a physician. Get medical attention immediately.
Inhalation	Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	May cause stomach pain or vomiting.
Skin contact	Prolonged contact may cause redness, irritation and dry skin.
Eye contact	May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures**5.1. Extinguishing media**

Suitable extinguishing media Carbon dioxide (CO₂). Alcohol-resistant foam. Powder. Water spray, fog or mist.

BIJLARD GIETLIJM 2921 R

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is highly flammable. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³.

Hazardous combustion products When heated, vapours/gases hazardous to health may be formed.

5.3. Advice for firefighters

Protective actions during firefighting Move containers from fire area if it can be done without risk. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

Special protective equipment for firefighters Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Eliminate all sources of ignition. Avoid inhalation of vapours and contact with skin and eyes. Take precautionary measures against static discharges.

6.2. Environmental precautions

Environmental precautions Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. Do not discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. Collect and dispose of spillage as indicated in Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Provide adequate ventilation. Avoid contact with skin and eyes. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Protect from freezing and direct sunlight. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store in tightly-closed, original container.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

BIJLARD GIETLIJM 2921 R

Occupational exposure limits

BUTANONE

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 600 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 300 ppm(Sk) 899 mg/m³(Sk)

TOLUENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 191 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 384 mg/m³

Sk

ROSIN

Long-term exposure limit (8-hour TWA): WEL 0,05 mg/m³

Short-term exposure limit (15-minute): WEL 0,15 mg/m³

Sen

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Sk

Hydrocarbons,C7, n-alkanes, isoalkanes, cyclics

Long-term exposure limit (8-hour TWA): OEL = Occupational Exposure Limit 500 ppm 2085 mg/m³

ethylbenzene

Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m³

Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m³

Sk

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

Sen = Capable of causing occupational asthma.

Sk = Can be absorbed through skin.

Ingredient comments

WEL = Workplace Exposure Limits

Hydrocarbons, C6-C7,n-alkanes, isoalkanes,cyclics, <5% n-hexane

DNEL

Consumer - Oral; Long term systemic effects: 699 mg/kg/day

Industry - Oral; Long term systemic effects: 2035 mg/kg/day

Consumer - Dermal; Long term systemic effects: 699 mg/kg/day

Industry - Dermal; Long term systemic effects: 773 mg/kg/day

Consumer - Inhalation; Long term systemic effects: 608 mg/m³

BUTANONE (CAS: 78-93-3)

DNEL

Industry - Inhalation; Short term local effects: 600 mg/kg/day

Industry - Dermal; : 1161 mg/kg/day

Consumer - Dermal; : 412 mg/kg/day

Consumer - Inhalation; : 106 mg/m³

Consumer - Dermal; Long term systemic effects: 31 mg/kg

BIJLARD GIETLIJM 2921 R

PNEC	- Fresh water; 55.8 mg/l
	- Sediment (Marinewater); 284.74 mg/kg
	- Soil; 22.5 mg/kg
	marine water; 55.8 mg/l
	Intermittent release; 55.8 mg/l
	Sediment (Freshwater); 284.7 mg/kg
	STP; 709 mg/l
	- Food. Secondary poisoning; 1000 mg/kg

TOLUENE (CAS: 108-88-3)

DNEL	Human being - ; Short term systemic effects: 226 mg/m ³
	Human being - Inhalation; Short term local effects: 226 mg/m ³
	Human being - Dermal; Long term systemic effects: 226 mg/m ³
	Human being - Inhalation; Long term systemic effects: 226 mg/kg
	Human being - Inhalation; Long term systemic effects: 56.5 mg/m ³
	Human being - Oral; Long term systemic effects: 8.13 mg/kg

PNEC	Sediment (Freshwater); 0.68 mg/l
	Sediment (Marinewater); 0.68 mg/l
	STP; 13.61 mg/l
	Sediment (Freshwater); 16.39 mg/kg
	Sediment (Freshwater); 16.39 mg/kg
	Soil; 2.89 mg/kg

Hydrocarbons, C6 isoalkanes <5% n-hexane

DNEL	Consumer - Oral; Long term systemic effects: 1301 mg/kg/day
	Consumer - Dermal; Long term systemic effects: 1377 mg/kg/day
	Industry - Dermal; Long term systemic effects: 13964 mg/kg/day
	Consumer - Inhalation; Long term systemic effects: 1131 mg/m ³
	Industry - Inhalation; Long term systemic effects: 5306 mg/m ³

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

DNEL	Industry - Dermal; Long term : 300 mg/kg/day
	Industry - Inhalation; Long term : 2085 mg/m ³
	Consumer - Dermal; Long term : 149 mg/kg/day
	Consumer - Inhalation; Long term : 447 mg/m ³

PNEC	No PNEC data available
-------------	------------------------

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. Dust may form explosive mixture with air. Take precautionary measures against static discharges.

Eye/face protection

The following protection should be worn: Chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

BIJLARD GIETLIJM 2921 R

Other skin and body protection	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear apron or protective clothing in case of contact.
Hygiene measures	Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station. Provide eyewash station and safety shower. Wash contaminated clothing before reuse. Use appropriate skin cream to prevent drying of skin. Wash promptly if skin becomes contaminated. Change work clothing daily before leaving workplace.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P3.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Red.
Odour	Characteristic.
Odour threshold	Not available.
pH	Not applicable.
Melting point	Not available.
Initial boiling point and range	60 - 110°C
Flash point	~ -25°C
Evaporation rate	moderate
Evaporation factor	Not available.
Upper/lower flammability or explosive limits	No information available.
Other flammability	No information available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	~ 0.8 @ 20°C
Bulk density	Not available.
Solubility(ies)	Insoluble in water. Soluble in the following materials: Organic solvents.
Partition coefficient	Not available.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not available.
Viscosity	200 cP @ 20°C
Explosive properties	No information available.
Comments	Information given is applicable to the product as supplied. Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.

BIJLARD GIETLIJM 2921 R

Density

Relative vapour density

Water solubility

Viscosity, dynamic

9.2. Other information

Refractive index Not applicable.

Particle size Not available.

Molecular weight Not applicable.

Volatility Not available.

Critical temperature Not available.

Solvent content:

Volatile organic compound Not available.

Solids content:

Water:

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not determined.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. When heated, vapours/gases hazardous to health may be formed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects Information given for the mixture in sect 3 is based upon the results of the calculation method. Some of the information given is also taken from data given for the individual ingredients of the mixture.

Acute toxicity - oral

Notes (oral LD₅₀) Not determined.

Acute toxicity - dermal

BIJLARD GIETLIJM 2921 R

Notes (dermal LD₅₀)	Not determined.
<u>Acute toxicity - inhalation</u>	
Notes (inhalation LC₅₀)	Not determined.
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Based on available data the classification criteria are not met.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Causes eye irritation.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Based on available data the classification criteria are not met.
<u>Skin sensitisation</u>	
Skin sensitisation	May cause sensitisation by skin contact.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Genotoxicity - in vivo	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	Based on available data the classification criteria are not met.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	May cause drowsiness or dizziness.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Based on available data the classification criteria are not met.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.
<u>General information</u>	
General information	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Inhalation	Vapour from this product may be hazardous by inhalation. Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	Liquid irritates mucous membranes and may cause abdominal pain if swallowed.
Skin contact	Prolonged contact may cause dryness of the skin. Repeated exposure may cause skin dryness or cracking.
Eye contact	May cause temporary eye irritation.
Acute and chronic health hazards	Prolonged contact may cause redness, irritation and dry skin. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis and skin cancer. Prolonged or repeated exposure to vapours in high concentrations may cause the following adverse effects: Central and/or peripheral nervous system damage. Brain damage.
Route of exposure	Skin and/or eye contact Ingestion. Inhalation

BIJLARD GIETLIJM 2921 R

Target organs	Brain Respiratory system, lungs Mucous membranes Skin
Medical symptoms	Skin irritation. Irritation of eyes and mucous membranes. Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting.
Medical considerations	Skin disorders and allergies. Convulsions. Central nervous system depression. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Toxicological information on ingredients.

Hydrocarbons, C6-C7,n-alkanes, isoalkanes,cyclics, <5% n-hexane

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >5000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2000 mg/kg, Dermal, Rabbit

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LD₅₀ >20 mg/l, Inhalation, Rat

Skin corrosion/irritation

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation No information available.

Skin sensitisation

Skin sensitisation No information available.

Germ cell mutagenicity

Genotoxicity - in vitro No information available.

Genotoxicity - in vivo No information available.

Carcinogenicity

Carcinogenicity No information available.

Target organ for carcinogenicity No specific target organs known.

IARC carcinogenicity Not listed.

Reproductive toxicity

Reproductive toxicity - fertility No information available.

Reproductive toxicity - development This substance has no evidence of toxicity to reproduction.

Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness.

BIJLARD GIETLIJM 2921 R

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways.

BUTANONE

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >2193 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >5000 mg/kg, Dermal, Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 34.0

Species Rat

ATE inhalation (vapours mg/l) 34.0

Skin corrosion/irritation

Skin corrosion/irritation Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation Causes eye irritation.

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Carcinogenicity in humans is not expected.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure A single exposure may cause the following adverse effects: Drowsiness, dizziness, disorientation, vertigo.

Target organs Central nervous system

BIJLARD GIETLIJM 2921 R

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

TOLUENE

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ 636 mg/kg, Oral, Rat Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LD₅₀ 49 g/m³, Inhalation, Rat

Skin corrosion/irritation

Skin corrosion/irritation Severe skin irritation.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development Repr. 2 - H361d Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure STOT RE 2 - H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways.

ROSIN

BIJLARD GIETLIJM 2921 R

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >2000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2000 mg/kg, Dermal, Rat

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Data lacking.

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

Hydrocarbons, C6 isoalkanes <5% n-hexane

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 16,750.0

Species Rat

Notes (oral LD₅₀) LD₅₀ >5000 ml/kg, Oral, Rat

ATE oral (mg/kg) 16,750.0

BIJLARD GIETLIJM 2921 R

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀) 3,350.0
mg/kg)

Species Rabbit

Notes (dermal LD₅₀) LD₅₀ 5 mg/kg, Dermal, Rabbit

ATE dermal (mg/kg) 3,350.0

Acute toxicity - inhalation

Acute toxicity inhalation 259,354.0
(LC₅₀ vapours mg/l)

Species Rat

Notes (inhalation LC₅₀) LC₅₀ 20 mg/l, Inhalation, (Vapour), Rat

ATE inhalation (vapours 259,354.0
mg/l)

Skin corrosion/irritation

Skin corrosion/irritation No oedema (0).

Animal data Erythema/eschar score: 0.8 Rabbit

Serious eye damage/irritation

Serious eye Redness of the conjunctivae Rabbit 0 Oedema of the conjunctivae Rabbit 0.33 Iris
damage/irritation score: Normal (0). Cornea score: No ulceration or opacity (0).

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Not available.

Reproductive toxicity

Reproductive toxicity - Based on available data the classification criteria are not met.
fertility

Reproductive toxicity - Based on available data the classification criteria are not met.
development

Specific target organ toxicity - single exposure

STOT - single exposure Not applicable.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not applicable.

Aspiration hazard

BIJLARD GIETLIJM 2921 R

Aspiration hazard May be fatal if swallowed and enters airways.

Hydrocarbons,C7, n-alkanes, isoalkanes, cyclics

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >5480 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2920 mg/kg, Dermal, Rat

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LC₅₀ >23300 mg/cm², Inhalation, (Vapour), Rat

Skin corrosion/irritation

Skin corrosion/irritation Irritating to skin.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met. Redness of the conjunctivae Rabbit 0 Oedema Conjunctivae score: Normal (0). Rabbit

Respiratory sensitisation

Respiratory sensitisation Not sensitising. Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity No evidence of carcinogenicity in animal studies.

Reproductive toxicity

Reproductive toxicity - fertility Not applicable.

Reproductive toxicity - development Not applicable.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Aspiration hazard if swallowed. May be fatal if swallowed and enters airways.

Inhalation

Central nervous system depression. Vapours may cause headache, fatigue, dizziness and nausea. Overexposure may depress the central nervous system, causing dizziness and intoxication.

BIJLARD GIETLIJM 2921 R

Ingestion	The product irritates mucous membranes and may cause abdominal discomfort if swallowed. May cause nausea, headache, dizziness and intoxication. Central nervous system depression.
Skin contact	Irritating to skin.
Eye contact	The product is strongly irritating to eyes and skin.

SECTION 12: Ecological information

Ecotoxicity The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Acute aquatic toxicity

Chronic aquatic toxicity

Ecological information on ingredients.

Hydrocarbons,C7, n-alkanes, isoalkanes, cyclics

Ecotoxicity Toxic to aquatic life with long lasting effects.

12.1. Toxicity

Toxicity The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment. Information given for the mixture in sect 3 is based upon the results of the calculation method. Some of the information given is also taken from data given for the individual ingredients of the mixture.

Acute aquatic toxicity

Acute toxicity - fish Not determined.

Acute toxicity - aquatic invertebrates Not determined.

Acute toxicity - aquatic plants Not determined.

Acute toxicity - microorganisms Not determined.

Acute toxicity - terrestrial Not determined.

Chronic aquatic toxicity

Chronic toxicity - fish early life stage Not determined.

Short term toxicity - embryo and sac fry stages Not determined.

Chronic toxicity - aquatic invertebrates Not determined.

Chronic toxicity in fish

Ecological information on ingredients.

Hydrocarbons, C6-C7,n-alkanes, isoalkanes,cyclics, <5% n-hexane

Acute aquatic toxicity

Acute toxicity - fish LC50, : 1-10 mg/l,

BIJLARD GIETLIJM 2921 R

Acute toxicity - aquatic plants EC₅₀, : 10-100 ,

Chronic aquatic toxicity

Chronic toxicity - fish early life stage The substance is readily biodegradable.

BUTANONE**Acute aquatic toxicity**

Acute toxicity - fish LC₅₀, 48 hours: > 100 mg/l, Leuciscus idus (Golden orfe)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: >100 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: >100 mg/l, Pseudokirchneriella subcapitata

Acute toxicity - microorganisms EC₃, 16 hours: 1150 mg/l, Bacteria

TOLUENE**Acute aquatic toxicity**

Acute toxicity - fish LC₅₀, 96 hours: >1 <=10 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: >1<=10 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: >100 mg/l, Algae

Zinc Oxide**Acute aquatic toxicity**

LE(C)₅₀ 0.1 < L(E)C₅₀ ≤ 1

M factor (Acute) 1

Chronic aquatic toxicity

NOEC 0.01 < NOEC ≤ 0.1

Degradability Non-rapidly degradable

M factor (Chronic) 1

Hydrocarbons, C6 isoalkanes <5% n-hexane**Acute aquatic toxicity**

Acute toxicity - fish LC₅₀, >: > 1 mg/l,

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 1680 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, : 10-100 mg/l,

Hydrocarbons,C7, n-alkanes, isoalkanes, cyclics

BIJLARD GIETLIJM 2921 R

Toxicity The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hour: >13.4 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 3 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 10 mg/l,

Chronic aquatic toxicity

Chronic toxicity - fish early life stage NOEC, 28 days: 1.53 mg/l, Oncorhynchus mykiss (Rainbow trout)

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 1 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Phototransformation Not relevant.

Stability (hydrolysis) Not determined.

Biodegradation Not determined.

Biological oxygen demand Not determined.

Chemical oxygen demand Not determined.

Ecological information on ingredients.

Hydrocarbons, C6-C7,n-alkanes, isoalkanes,cyclics, <5% n-hexane

Persistence and degradability The product is readily biodegradable.

Biodegradation The substance is readily biodegradable.

BUTANONE

Persistence and degradability The product is biodegradable.

Biodegradation >60% 28, days

TOLUENE

Effect on Effluent Treatment No data available

Hydrocarbons,C7, n-alkanes, isoalkanes, cyclics

Biodegradation - 98: 28 days

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

BIJLARD GIETLIJM 2921 R

Partition coefficient Not available.

Ecological information on ingredients.

Hydrocarbons, C6-C7,n-alkanes, isoalkanes,cyclics, <5% n-hexane

Bioaccumulative potential Data lacking.

Partition coefficient No information available.

BUTANONE

Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

Adsorption/desorption coefficient Not determined.

Henry's law constant Not determined.

Surface tension Not determined.

Environmental distribution

Ecological information on ingredients.

Hydrocarbons, C6-C7,n-alkanes, isoalkanes,cyclics, <5% n-hexane

Mobility No data available.

BUTANONE

Mobility Not considered mobile.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

Hydrocarbons, C6-C7,n-alkanes, isoalkanes,cyclics, <5% n-hexane

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

BUTANONE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not known.

Ecological information on ingredients.

Hydrocarbons, C6-C7,n-alkanes, isoalkanes,cyclics, <5% n-hexane

BIJLARD GIETLIJM 2921 R

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Waste is suitable for incineration. The generation of waste should be minimised or avoided wherever possible. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents.

Product

Uncleaned packaging

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1133
UN No. (IMDG)	1133
UN No. (ICAO)	1133
UN No. (ADN)	1133

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	ADHESIVES
Proper shipping name (IMDG)	ADHESIVES
Proper shipping name (ICAO)	ADHESIVES
Proper shipping name (ADN)	ADHESIVES

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II

BIJLARD GIETLIJM 2921 R

ICAO packing group II

ADN packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-E, S-D

ADR transport category 2

Emergency Action Code •3YE

Hazard Identification Number (ADR/RID) 33

Tunnel restriction code (D/E)

Segregation Code

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Transport/Additional information Marine Pollutant Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Carriage of Dangerous Goods and use of Transportable Pressure Equipment Regulations 2009 as amended(SI 2009/1348)
The Control of Substances Hazardous to Health Regulations 2002. (SI 2002 No 2677) as amended

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Commission Regulation (EU) No 2015/830 of 28 May 2015.

Guidance EH40/2005 Workplace exposure limits
L131 Approved Classification and Labelling Guide (Sixth Edition)

Health and environmental listings Contains n-Hexane, CAS No 110-54-3, which has been added to the Candidate List of substances of very high concern.

Authorisations (Annex XIV Regulation 1907/2006) No specific authorisations are known for this product.

BIJLARD GIETLIJM 2921 R

Restrictions (Annex XVII Regulation 1907/2006)

No specific restrictions on use are known for this product. This product contains Toluene which is listed in Entry 48 Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information	Only trained personnel should use this material.
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	23/04/2026
Revision	9
Supersedes date	23/11/2023
SDS status	Approved.
Hazard statements in full	<p>H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H361d Suspected of damaging the unborn child. H373 May cause damage to organs (Hearing organs) through prolonged or repeated exposure. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH208 Contains ROSIN. May produce an allergic reaction.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.