Bijlard Super Bond Activator

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 7/29/2026 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	:	Mixture
Product name	:	Bijlard Super Bond Activator
UFI	:	886Y-58QR-N009-H1EJ
Type of product	:	Activator
Vaporizer	:	Aerosol
Product group	:	Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Industrial/Professional use spec	:	Professional uses Industrial use
Use of the substance/mixture	:	Activator

Title	Life cycle stage	Use descriptors
Bijlard Super Bond Activator	Professional	SU0, PC1, PROC0

Full text of use descriptors: see section 16

1.3. Details of the supplier of the safety data sheet

Bijlard International
Platinastraat 141
2718 SR Zoetermeer
The Netherlands
T +31 (0) 79 343 75 38
info@bijlard.com, www.bijlard.com

1.4. Emergency telephone number

Country/Area	Organisation	Emergency number
United Kingdom	National Poisons Information Service (Birmingham Centre). City Hospital. Dudley Road B18 7QH Birmingham.	0344 892 0111 Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Causes serious eye damage. May cause drowsiness or dizziness.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :

GHS02 GHS07

Signal word (CLP) : Danger

Contains : ISOPROPYL ALCOHOL

Hazard statements (CLP) : H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Extra phrases : Derogation from labelling requirements according to CLP Article 23(c); Annex I Part 1 Section 1.3.3.
For professional users only.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Product name	Product identifier	% w/w (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ISOPROPYL ALCOHOL substance with national workplace exposure limit(s) (GB)	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558-25	50 – 75	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.
Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : In case of doubt or persistent symptoms, consult always a physician.

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical attention.

First-aid measures after skin contact : Wash skin with mild soap and water. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact	:	Rinse immediately with plenty of water, also under the eyelids. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	:	IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Seek medical attention if ill effect develops.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	:	May cause drowsiness or dizziness.
Symptoms/effects after inhalation	:	Inhalation of vapors may cause drowsiness, dizziness, cough and headache. Overexposure may cause : Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	:	Causes mild skin irritation. May cause an allergic skin reaction. Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).
Symptoms/effects after eye contact	:	Causes eyes to water. mild eye irritation. stinging.
Symptoms/effects after ingestion	:	Swallowing material may cause irritation of the gastrointestinal lining, nausea, vomiting, diarrhea, and abdominal pain. Dizziness, headaches, nausea.
Chronic symptoms	:	Prolonged exposure to small concentrations may result in pulmonary oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	:	Dry chemical, CO2, or water spray or regular foam. Making extinguishing agents environment-friendly.
Unsuitable extinguishing media	:	high volume water jet or water based extinguishing media.

5.2. Special hazards arising from the substance or mixture

Fire hazard	:	Extremely flammable aerosol. Flammable vapour/air mixtures may be formed.
Explosion hazard	:	Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	:	Combustion products may include the following: carbon oxides (CO, CO2) (carbon monoxide, carbon dioxide) nitrogen oxides (NO, NO_2 etc.).

5.3. Advice for firefighters

Precautionary measures fire	:	Do not approach fire except upwind and only with proper skin and respiratory protection (supplied air only).
Firefighting instructions	:	Use water spray or fog for cooling exposed containers. Do not enter fire area without proper protective equipment, including respiratory protection. Fight fire remotely due to the risk of explosion.
Protection during firefighting	:	Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	:	Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	:	Wear personal protective equipment.

For non-emergency personnel

Emergency procedures	:	Evacuate unnecessary personnel.

6.2. Environmental precautions

Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

For containment	:	Collect spillage.

Methods for cleaning up	:	No open flames. No smoking. Wear recommended personal protective equipment. Mechanically recover the product. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).
Other information	:	Facility must be capable of handling aerosol cans.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	:	In use, may form flammable vapour-air mixture. Do not pierce or burn, even after use. May explode on heating. Vapours may cause drowsiness and dizziness.
Precautions for safe handling	:	Avoid breathing vapours, mist, spray. Avoid contact with skin, eyes and clothing. Do not spray into eyes. Ensure good ventilation of the work station. No open flames. No smoking.
Hygiene measures	:	Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	:	Comply with applicable regulations.
Storage conditions	:	Keep only in the original container in a cool, well-ventilated place. Keep in fireproof place. Keep away from ignition sources.
Incompatible products	:	Strong acids. Strong bases. Strong oxidizing agents. Aluminium.
Incompatible materials for storage	:	Heat sources. Direct sunlight. flames or sparks. hot surfaces. open flames.
Storage temperature	:	< 45 °C
Heat and ignition sources	:	Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.
Storage area	:	Fireproof storeroom. Keep out of direct sunlight.
Packaging materials	:	Keep only in the original container.

7.3. Specific end use(s)

Activator.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

ISOPROPYL ALCOHOL (67-63-0)	
United Kingdom - Occupational Exposure Limits	
Local name	Propan-2-ol
WEL TWA (OEL TWA)	999 mg/m³
	400 ppm
WEL STEL (OEL STEL)	1250 mg/m³
	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

DNEL and PNEC

ISOPROPYL ALCOHOL (67-63-0)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	1000 mg/m³
Long-term - systemic effects, dermal	888 mg/kg bodyweight/day

ISOPROPYL ALCOHOL (67-63-0)	
Long-term - systemic effects, inhalation	500 mg/m³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	178 mg/m³
Acute - systemic effects, oral	51 mg/kg bw/day
Long-term - systemic effects,oral	26 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	89 mg/m³
Long-term - systemic effects, dermal	319 mg/kg bodyweight/day

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:
Provide adequate ventilation. Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:
Protective goggles.
Personal protective equipment symbol(s):

Eye and face protection

Eye protection:
Recommendation: Wear eye glasses with side protection according to EN 166.

Skin protection

Skin and body protection:
Normal overalls

Hand protection:
Recommendation: Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear. Gloves. uitable chemical resistant safety gloves (EN 374) also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374): e.g. nitrile rubber (>=0.4 mm), butyl rubber (>=0.7 mm) and others.

Other skin protection
Materials for protective clothing:
Wear suitable protective clothing.

Respiratory protection

Respiratory protection:
In case of inadequate ventilation wear respiratory protection. Recommended: Filter A (brown). (EN 14387). Reusable half mask

Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.
Other information:
Do not eat, drink or smoke during use. Contact with skin through cellulose based fabrics (i.e cotton, rayon, linen, viscose) generates heat and may cause burns.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid

Colour	:	Colourless.
Odour	:	alcoholically.
Odour threshold	:	Not available
Melting point	:	≈ 89 °C
Freezing point	:	Not available
Boiling point	:	82 °C
Flammability	:	Flammable vapour/air mixtures may be formed Extremely flammable
Explosive properties	:	Pressurised container: May burst if heated. Vapours may form flammable and explosive mixture with air.
Oxidising properties	:	Not oxidising.
Lower explosion limit	:	≈ 2 Vol-%
Upper explosion limit	:	≈ 10 Vol-%
Flash point	:	-40 °C
Auto-ignition temperature	:	399 °C @1013hPa
Decomposition temperature	:	Not available
pH	:	Not available
Viscosity, kinematic	:	2.2 mm²/s Viscosity, kinematic in 10^{-6} m²/s (40 °C) ISO 3104/3105
Solubility	:	Water: ≈ 1000 g/l In water, material soluble
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Partition coefficient n-octanol/water (Log Pow)	:	< 3 (estimated value)
Vapour pressure	:	≈ 412 kPa @20°C
Vapour pressure at 50°C	:	Not available
Density	:	≈ 0.799 g/cm³ @20°C
Relative density	:	0.8
Relative vapour density at 20°C	:	≈ 2
Particle characteristics	:	Not applicable

9.2. Other information

Information with regard to physical hazard classes

% of flammable ingredients	:	100 %

Other safety characteristics

VOC content	:	695 g/l 99% Flammable ingredients
Other properties	:	Gas/vapour heavier than air at 20°C

SECTION 10: Stability and reactivity

10.1. Reactivity

Pressurised container: May burst if heated.

10.2. Chemical stability

Stable in use and storage conditions as recommended in item 7. In use may form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

Can form explosive mixture with air. Bursting aerosol containers may be propelled from a fire at high speed.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agent. Aluminium.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Combustion products may include the following: carbon oxides (CO, CO2) (carbon monoxide, carbon dioxide) nitrogen oxides (NO, NO_2 etc.).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

ISOPROPYL ALCOHOL (67-63-0)	
LD50 oral rat	5.84 g/kg OECD 401
LD50 dermal rabbit	16.4 ml/kg OECD 402
LC50 Inhalation - Rat [ppm]	> 10000 ppm 6 h; OECD 403
ATE oral	5840 mg/kg bodyweight

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

ISOPROPYL ALCOHOL (67-63-0)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness.

ISOPROPYL ALCOHOL (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

ISOPROPYL ALCOHOL (67-63-0)	
NOAEC (inhalation, rat, vapour, 90 days)	5000 ppm

Aspiration hazard : Not classified

Bijlard Super Bond Activator	
Vaporizer	Aerosol
Viscosity, kinematic	2.2 mm²/s Viscosity, kinematic in 10^{-6} m²/s (40 °C) ISO 3104/3105

ISOPROPYL ALCOHOL (67-63-0)	
Viscosity, kinematic	2.658 mm²/s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short–term (acute) : Not classified
Hazardous to the aquatic environment, long–term (chronic) : Not classified

ISOPROPYL ALCOHOL (67-63-0)	
LC50 - Fish	10000 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas

ISOPROPYL ALCOHOL (67-63-0)	
EC50 - Crustacea	> 10000 mg/l 24 h; Daphnia magna; OECD 202
EC50 - Crustacea [2]	> 10 g/l (24h)
EC50 72h - Algae	9.17 g/l
NOEC chronic algae	1.8 g/l
Additional information	:

12.2. Persistence and degradability

Bijlard Super Bond Activator	
Persistence and degradability	Rapidly degradable

ISOPROPYL ALCOHOL (67-63-0)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.19 – 1.72 g O_2/g substance
Chemical oxygen demand (COD)	2.23 g O_2/g substance
Biodegradation	53 % 5 d; EU Method C.5; EU Method C.6

12.3. Bioaccumulative potential

Bijlard Super Bond Activator	
Partition coefficient n-octanol/water (Log Pow)	< 3 (estimated value)

ISOPROPYL ALCOHOL (67-63-0)	
BCF - Other aquatic organisms [1]	1.015 l/kg
Partition coefficient n-octanol/water (Log Pow)	≈ 0.05 @ 25 °C
Partition coefficient n-octanol/water (Log Kow)	0.05 @ 25°C

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Bijlard Super Bond Activator	
Other information	Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Ensure aerosol cans are sprayed completely empty (including propellant).
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not burn empty packaging. Do not cut using a blowtorch.
Ecological waste information : Avoid release to the environment.

European List of Waste (LoW, EC 2000/532) : 15 01 10* - packaging containing residues of or contaminated by dangerous substances
08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

HP Code : HP3 - "Flammable:"
– flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
– flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
– flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
– flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
– water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
– other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS	UN 1950 Aerosols, flammable	UN 1950 AEROSOLS	UN 1950 AEROSOLS
14.3. Transport hazard class(es)				
2.1	Not applicable	Not applicable	Not applicable	Not applicable
	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available.				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F
Special provisions (ADR) : 190, 327, 344, 625
Limited quantities (ADR) : 1l
Excepted quantities (ADR) : E0
Packing instructions (ADR) : P207, LP200
Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR)	:	MP9
Transport category (ADR)	:	2
Special provisions for carriage - Packages (ADR)	:	V14
Special provisions for carriage - Loading, unloading and handling (ADR)	:	CV9, CV12
Special provisions for carriage - Operation (ADR)	:	S2
Tunnel restriction code (ADR)	:	D

Transport by sea
No data available

Air transport
No data available

Inland waterway transport
No data available

Rail transport
No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Not listed on the Ozone Depletion list (Regulation EU 2024/590)
Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 695 g/l 99% Flammable ingredients

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out for the substance or the mixture by the supplier

SECTION 16: Other information

Abbreviations and acronyms:	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DNEL	Derived-No Effect Level
EC50	Median effective concentration
LC50	Median lethal concentration
LD50	Median lethal dose
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
STP	Sewage treatment plant
vPvB	Very Persistent and Very Bioaccumulative

Other information : DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H- and EUH-statements:	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Full text of use descriptors	
PC1	Adhesives, sealants
PROC0	Other
SU0	Other

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Aerosol 1	H222;H229	On basis of test data
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.